



01 FLOOR ENCLOSURES

02 WALL MOUNT ENCLOSURES

03 OPEN FRAME RACKS

04 EQUIPMENT SHELVING

05 CABLE MANAGERS

06 ACCESSORIES

07 CABLE TRAY SYSTEM

Product Catalog

ABOUT



Our Company

Quest Manufacturing Company is an established Enclosure & Rack manufacturer offering supply chain solutions to our distributors worldwide. Quest provides a stable source of competitively priced quality products for industries servicing installation of Networks; Telecommunications; Broadcast; Security Systems; Home Entertainment; MRO and OEM commercial and residential markets.

Our Products

Quest Manufacturing Company produces quality products for most installation requirements in our ISO 9001 factory, providing our customers best quality and value at a cost-effective price. Our product offering includes a wide selection of floor and wall mount racks and enclosures, as well as a complete line of enclosure accessories including: shelving; cable organizers; power distribution units; cooling fan units and more. Only the highest quality raw materials are used in the manufacture of Quests' metal line of products. In most cases cold-rolled steel is used in the manufacture of our products and our enclosures meet or exceed EIA-310D standards. Floor enclosures may be shipped fully assembled or to reduce customer shipping costs, are also available in knockdown shipping cartons.

Our Service

Quest Manufacturing Company is committed to world-class customer service, and our manufacturing philosophy is one of creative design and high-quality products. Quality starts with vast engineering resources, state-of-the-art equipment and exacting quality control procedures. The latest Computer Aided Design software is used to design all facets of our product line. Quest utilizes computer-controlled laser cutting and forming equipment in its manufacturing processes assuring precise fit and finish and is completely vertically integrated with machine-shops and proprietary electrostatic paint shop.

MAKING TECHNOLOGY WORK!

www.QuestManufacturing.net

© QUEST MANUFACTURING Co.
MIAMI, FL USA

PRODUCT ASSURANCE

Enclosures, Racks & Accessories (excluding electrical products)



Quest Manufacturing Company warrants its metal fabricated products which include all enclosures, racks, shelves, wire management and rack accessories to be free from any manufacturing and/or material defects for a period of five years following delivery of original purchase.

Electrical Products



Quest Manufacturing Company warrants its rack electrical accessories which include all Power & Surge Strips, Power Distribution Units (PDU's) and Fan enclosures to be free from any manufacturing and/or material defects for a period of one year following delivery of original purchase.

This warranty will not extend to any product that has been subject to misuse, negligence, accident, improper installation, or used in violation of instructions; including but not limited to: electrical irregularities, lightning or power-line related damage, paint scratches or other unusual occurrences.

Quest Manufacturing Company's liability shall be limited to the repair and/or replacement of products and assumes no liability with respect to the use of the products including: merchantability or fitness for a particular use; assumes no liability for any consequential damages caused directly or indirectly by the use of its products or from any other cause if proven defective. This warranty extends to all Quest Manufacturing products.

For more detailed information regarding our warranty programs visit our website at:

questmanufacturing.net/warranty-certifications/



TABLE OF CONTENTS

Section 01 FLOOR ENCLOSURES

NEW DEPTH SIZES

| | Page# |
|--|-------|
| Intro to Quest Floor Enclosures..... | 01-02 |
| 4XX SERIES W/SMOKED ACRYLIC FRONT DOOR | |
| 400 Series (19" w x 24" d) | 03-04 |
| 410 Series (19" w x 32" d) | 05-06 |
| 420 Series (27.5" w x 32" d) | 07-08 |
| 430 Series (27.5" w x 36" d) | 09-10 |
| 7XX SERIES W/VENTED STEEL MESH FRONT DOOR | |
| 700 Series (19" w x 24" d) | 11-12 |
| 710 Series (19" w x 32" d) | 13-14 |
| 720 Series (27.5" w x 32" d) | 15-16 |
| 730 Series (27.5" w x 36" d) | 17-18 |
| 740 Series (27.5" w x 42" d) | 19-20 |
| HOME THEATER ENCLOSURES | |
| 3ft & 5ft HT Enclosure (23" w x 24" d) | 21-22 |

Section 02 WALL MOUNT ENCLOSURES

NEW EXTENDED DEPTH SIZES

| | |
|--|-------|
| Intro to Quest Wall Mount Enclosures | 23-24 |
| 200 Series - Removable Side Panels..... | 25-26 |
| <i>Honeycomb™</i> | |
| NEW 210 Series - Honeycomb Meshed Steel | 27-28 |
| 300 Series - Swing-Out Design | 29-30 |
| EZ-Series 600 - EZ-Assembly | 31-32 |
| DVR Security Enclosures | 33-34 |

Section 03 OPEN FRAME RACKS

NEW BRACKET DESIGN

| | |
|--|-------|
| Intro to Quest Open Frame Racks | 35-36 |
| OPEN FRAME FLOOR RACKS | |
| 4-Post Steel Adjustable Rack | 37-38 |
| 2-Post Aluminum Floor Mount Rack | 39-40 |
| 2-Post Steel Floor Mount Rack | 39-40 |
| 2-Post Steel Floor Rack with Casters | 39-40 |
| OPEN FRAME WALL MOUNT RACKS | |
| 2-Post Fixed Design | 41 |
| 2-Post Swing-Out Design | 41 |
| 2-Post Adjustable Swing-Out Design | 41 |
| OPEN FRAME WALL BRACKETS | |
| Non-Hinged Design | 42 |
| Hinged Design | 42 |

Section 04 EQUIPMENT SHELVING

| | Page# |
|---|-------|
| Intro to Quest Equipment Shelving | 43-44 |
| SLIDE-OUT & ADJUSTABLE SHELVES | |
| Locking Storage Drawers | 45 |
| Keyboard Shelves | 46 |
| Adjustable 4-Point Shelves | 47 |
| Slide-Out Vented Shelves | 48 |
| FIXED DUAL-SIDED SHELVES | |
| 1-Piece Vented Fixed Dual-Sided Shelves | 49 |
| 1-Piece Non-Vented Fixed Dual-Sided Shelves | 49 |
| 2-Piece Vented Split Fixed Dual-Sided Shelf | 49 |
| 2-Piece Non-Vented Fixed Dual-Sided Shelf | 49 |
| FIXED SINGLE-SIDED SHELVES | |
| 1-Piece Non-Vented Single-Sided Fixed Shelf | 50 |
| 2-Piece Non-Vented Single-Sided Fixed Shelf | 50 |

Section 05 CABLE MANAGERS

NEW LARGE OPENING FINGER DUCT

| | |
|--|-------|
| Finger Duct Cable Managers for Racks & Enclosures..... | 51-52 |
| Ring Style Cable Managers for Racks & Enclosures..... | 53 |


Section 06 ACCESSORIES

| | |
|---|----|
| FILLER PANELS | |
| 19" Brush Filler Panels for Racks & Enclosures | 54 |
| 19" Vented Filler Panels for Racks & Enclosures | 54 |
| 19" Non-Vented Filler Panels for Racks & Enclosures | 54 |
| AC POWER DISTRIBUTION UNITS | |
| Rack Mountable Vertical AC Power Strips | 55 |
| NEW: Rack Mountable Horizontal AC Surge Strips | 56 |
| VENTILATION DEVICES & MOUNTING HARDWARE | |
| Ventilation 4-Fan Rack Mount Unit | 57 |
| Single 4" Replacement Boxer Fans | 57 |
| Rails / Stabilizers / Cage Nuts / Screws & Washers | 57 |

Section 07 CABLE TRAY SYSTEM

NEW

| | |
|---|-------|
| CABLE TRAYS & J-HOOKS | |
| Wire Mesh Cable Trays | 58 |
| Heavy Duty Bolt Cutter | 58 |
| CABLE TRAY ACCESSORIES & HARDWARE | |
| Couplers | 59 |
| Mounting Accessories..... | 60 |
| Accessories & Hardware..... | 61 |
| CABLE TRAY CUTTING & BENDING GUIDES | |
| Configurations with Cable Tray & Accessories..... | 62-63 |





FLOOR ENCLOSURES

SECTION

01

400 SERIES
w/Acrylic Door

700 SERIES
w/Mesh Door

HOME THEATER





FLOOR ENCLOSURES

400 Smoked Acrylic Door Series **Page No.**

| | |
|--|--------------|
| 400 Series (19"w x 24"d Size Group) | 03-04 |
| 410 Series (19"w x 32"d Size Group) | 05-06 |
| 420 Series (27.5"w x 32"d Size Group) | 07-08 |
| 430 Series (27.5"w x 36"d Size Group) | 09-10 |

SECTION
01

700 Vented Steel Mesh Door Series **Page No.**

| | |
|--|--------------|
| 700 Series (19"w x 24"d Size Group) | 11-12 |
| 710 Series (19"w x 32"d Size Group) | 13-14 |
| 720 Series (27.5"w x 32"d Size Group) | 15-16 |
| 730 Series (27.5"w x 36"d Size Group) | 17-18 |
| 740 Series (27.5"w x 42"d Size Group) | 19-20 |

HT Home Theater Series **Page No.**

| | |
|---|--------------|
| HT Series (23"w x 24"d Size Group) | 21-22 |
|---|--------------|



FLOOR ENCLOSURES

400 SERIES – SMOKED ACRYLIC DOOR
19" X 24" SIZE GROUP

SECTION

01



NEW SIZES

400 Smoked Acrylic Door Series

400 Series

| | |
|--------------------------------------|---|
| External Rack Size Height | 45" (20U) 59" (28U) 69" (34U) 84" (42U) 88" (45U) |
| External Rack Size Width | 23" |
| External Rack Size Depth | 23" |
| Internal Mounting Format | 19" |
| Reversible Front Locking Door | Smoked Acrylic |
| Vented Side Panels | Yes |
| Dual Vented Locking Rear Doors | Yes |
| Reinforced Door Frame | Yes |
| Front & Rear Cage Rails | Yes |
| Dual Key Lock Sets (Doors & Sides) | 2 keys per set |
| Cable Access | Top:Cutouts Bottom:Panels |
| Electrostatic Powdercoat MicroFinish | Black |
| Preinstalled 80CFM 110V Fans | 2 |
| Casters | Yes |
| Leveling Feet | Yes |
| Ground Bus Bar | Yes |
| Green Grounding Wire | Yes |
| Cage Nuts, Screws & Washers | 30 each |
| Compliance | EIA-310D |
| Delivery Style | Assembled or Knockdown |

400 Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Rear Doors (AWG) | Front Door (AWG) | Base (AWG) |
|--------------|-------|----------------|-----------------|-------------------|-----------------|------------------|------------------|------------|
| FE4019-20-02 | Black | 20U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE4019-28-02 | Black | 28U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE4019-34-02 | Black | 34U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE4019-42-02 | Black | 42U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE4019-45-02 | Black | 45U | 16 | 18 | 18 | 18 | 18 | 16 |

FLOOR ENCLOSURES

400 SERIES – SMOKED ACRYLIC DOOR

19" X 24" SIZE GROUP



400 Smoked Acrylic Door Series

| Item No. ¹ | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) | Shipping Weight (Knockdown) ³ |
|-----------------------|--|----------------------------------|-----|-----|----------------------------------|-----|----------------|----------------------------|-----------------------------------|--|
| | | H | W | D | H | W | D ² | | | |
| FE4019-20-02 | 20U | 45" | 23" | 23" | 35" | 19" | 19.5" | 1400 | 147 | 114 |
| FE4019-28-02 | 28U | 59" | 23" | 23" | 49" | 19" | 19.5" | 1400 | 165 | 132 |
| FE4019-34-02 | 34U | 69" | 23" | 23" | 59.5" | 19" | 19.5" | 1400 | 180 | 147 |
| FE4019-42-02 | 42U | 84" | 23" | 23" | 74" | 19" | 19.5" | 1400 | 207 | 167 |
| FE4019-45-02 | 45U | 88" | 23" | 23" | 79" | 19" | 19.5" | 1400 | 218 | 185 |

1- To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.

2- Internal dimensions measure from front rails to back door. All 400 & 700 Series have an additional 2" usable space from rails to front door.

3- Knockdown Shipping Weight does not include weight of shipping pallet (approximately 60 lbs.)

SECTION

01

400 Dual Locking Rear Doors



These locking vented split doors allow mounting of enclosures in tighter spaces closer to the wall.

400 Removable Bottom Panels



Three removable panels for easy access to raised floors or for mounting equipment directly on the floor.

400 Adjustable Cage Nut Rails



Includes adjustable cage nut rails and cage nuts with standard #12-24 mounting screws. All cage nut rails are marked with an RU space index for easy alignment when mounting equipment.

400 Dual Pre-Installed Cooling Fans



Pre-Installed 110VAC 80CFM fan units keep equipment running cool.



SHIPPING OPTIONS

ASSEMBLED

UNASSEMBLED



Available to ship already assembled out-of-box, or ship unassembled in knockdown cartons for additional cost savings. To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.



FLOOR ENCLOSURES

410 SERIES – SMOKED ACRYLIC DOOR
19" X 32" SIZE GROUP

SECTION

01



NEW SIZES

410 Smoked Acrylic Door Series

410 Series

| | |
|--------------------------------------|---|
| External Rack Size Height | 45" (20U) 59" (28U) 69" (34U) 84" (42U) 88" (45U) |
| External Rack Size Width | 23" |
| External Rack Size Depth | 31" |
| Internal Mounting Format | 19" |
| Reversible Front Locking Door | Smoked Acrylic |
| Vented Side Panels | Yes |
| Dual Vented Locking Rear Doors | Yes |
| Reinforced Door Frame | Yes |
| Front & Rear Cage Rails | Yes |
| Dual Key Lock Sets (Doors & Sides) | 2 keys per set |
| Cable Access | Top:Cutouts Bottom:Panels |
| Electrostatic Powdercoat MicroFinish | Black |
| Preinstalled 80CFM 110V Fans | 2 |
| Casters | Yes |
| Leveling Feet | Yes |
| Ground Bus Bar | Yes |
| Green Grounding Wire | Yes |
| Cage Nuts, Screws & Washers | 30 each |
| Compliance | EIA-310D |
| Delivery Style | Assembled or Knockdown |

410 Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Rear Doors (AWG) | Front Door (AWG) | Base (AWG) |
|--------------|-------|----------------|-----------------|-------------------|-----------------|------------------|------------------|------------|
| FE4119-20-02 | Black | 20U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE4119-28-02 | Black | 28U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE4119-34-02 | Black | 34U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE4119-42-02 | Black | 42U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE4119-45-02 | Black | 45U | 16 | 18 | 18 | 18 | 18 | 16 |

FLOOR ENCLOSURES

410 SERIES – SMOKED ACRYLIC DOOR

19" X 32" SIZE GROUP



410 Smoked Acrylic Door Series

| Item No. ¹ | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) | Shipping Weight (Knockdown) ³ |
|-----------------------|--|----------------------------------|-----|-----|----------------------------------|-----|----------------|----------------------------|-----------------------------------|--|
| | | H | W | D | H | W | D ² | | | |
| FE4119-20-02 | 20U | 45" | 23" | 31" | 35" | 19" | 27.5" | 1400 | 171 | 138 |
| FE4119-28-02 | 28U | 59" | 23" | 31" | 49" | 19" | 27.5" | 1400 | 191 | 158 |
| FE4119-34-02 | 34U | 69" | 23" | 31" | 59.5" | 19" | 27.5" | 1400 | 209 | 176 |
| FE4119-42-02 | 42U | 84" | 23" | 31" | 74" | 19" | 27.5" | 1400 | 229 | 196 |
| FE4119-45-02 | 45U | 88" | 23" | 31" | 79" | 19" | 27.5" | 1400 | 246 | 213 |

1- To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.

2- Internal dimensions measure from front rails to back door. All 400 & 700 Series have an additional 2" usable space from rails to front door.

3- Knockdown Shipping Weight does not include weight of shipping pallet (approximately 60 lbs.)

SECTION


01

410 Dual Locking Rear Doors



These locking vented split doors allow mounting of enclosures in tighter spaces closer to the wall.

410 Removable Bottom Panels



Three removable panels for easy access to raised floors or for mounting equipment directly on the floor.

410 Adjustable Cage Nut Rails



Includes adjustable cage nut rails and cage nuts with standard #12-24 mounting screws. All cage nut rails are marked with an RU space index for easy alignment when mounting equipment.

410 Dual Pre-Installed Cooling Fans



Pre-Installed 110VAC 80CFM fan units keep equipment running cool.



SHIPPING OPTIONS

ASSEMBLED

UNASSEMBLED



Available to ship already assembled out-of-box, or ship unassembled in knockdown cartons for additional cost savings. To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.




FLOOR ENCLOSURES

420 SERIES – SMOKED ACRYLIC DOOR
27.5" X 32" SIZE GROUP

SECTION

01



NEW SIZES

420 Smoked Acrylic Door Series

420 Series

| | |
|--------------------------------------|------------------------------|
| External Rack Size Height | 84" (42U) 88" (45U) |
| External Rack Size Width | 27" |
| External Rack Size Depth | 31" |
| Internal Mounting Format | 19" |
| Reversible Front Locking Door | Smoked Acrylic |
| Vented Side Panels | Yes |
| Dual Vented Locking Rear Doors | Yes |
| Reinforced Door Frame | Yes |
| Front & Rear Cage Rails | Yes |
| Dual Key Lock Sets (Doors & Sides) | 2 keys per set |
| Cable Access | Top:Cutouts Bottom:Panels |
| Electrostatic Powdercoat MicroFinish | Black |
| Preinstalled 80CFM 110V Fans | 2 |
| Casters | Yes |
| Leveling Feet | Yes |
| Ground Bus Bar | Yes |
| Green Grounding Wire | Yes |
| Cage Nuts, Screws & Washers | 30 each |
| Compliance | EIA-310D |
| Delivery Style | Assembled or Knockdown |

420 Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Rear Doors (AWG) | Front Door (AWG) | Base (AWG) |
|--------------|-------|----------------|-----------------|-------------------|-----------------|------------------|------------------|------------|
| FE4219-42-02 | Black | 42U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE4219-45-02 | Black | 45U | 16 | 18 | 18 | 18 | 18 | 16 |

FLOOR ENCLOSURES

420 SERIES – SMOKED ACRYLIC DOOR

27.5" X 32" SIZE GROUP



420 Smoked Acrylic Door Series

| Item No. ¹ | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) | Shipping Weight (Knockdown) ³ |
|-----------------------|--|----------------------------------|-----|-----|----------------------------------|-----|----------------|----------------------------|-----------------------------------|--|
| | | H | W | D | H | W | D ² | | | |
| FE4219-42-02 | 42U | 84" | 27" | 31" | 74" | 19" | 27.5" | 1400 | 256 | 214 |
| FE4219-45-02 | 45U | 88" | 27" | 31" | 79" | 19" | 27.5" | 1400 | 262 | 227 |

1- To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.

2- Internal dimensions measure from front rails to back door. All 400 & 700 Series have an additional 2" usable space from rails to front door.

3- Knockdown Shipping Weight does not include weight of shipping pallet (approximately 60 lbs.)

SECTION


01

420 Dual Locking Rear Doors



These locking vented split doors allow mounting of enclosures in tighter spaces closer to the wall.

420 Removable Bottom Panels



Three removable panels for easy access to raised floors or for mounting equipment directly on the floor.

420 Adjustable Cage Nut Rails



Includes adjustable cage nut rails and cage nuts with standard #12-24 mounting screws. All cage nut rails are marked with an RU space index for easy alignment when mounting equipment.

420 Dual Pre-Installed Cooling Fans



Pre-Installed 110VAC 80CFM fan units keep equipment running cool.



SHIPPING OPTIONS

ASSEMBLED

UNASSEMBLED



Available to ship already assembled out-of-box, or ship unassembled in knockdown cartons for additional cost savings. To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.



FLOOR ENCLOSURES

430 SERIES – SMOKED ACRYLIC DOOR
27.5" X 36" SIZE GROUP

430 Smoked Acrylic Door Series

430 Series

| | |
|---------------------------|-----------|
| External Rack Size Height | 88" (45U) |
|---------------------------|-----------|

| | |
|--------------------------|-------|
| External Rack Size Width | 27.5" |
|--------------------------|-------|

| | |
|--------------------------|-----|
| External Rack Size Depth | 36" |
|--------------------------|-----|

| | |
|--------------------------|-----|
| Internal Mounting Format | 19" |
|--------------------------|-----|

| | |
|-------------------------------|----------------|
| Reversible Front Locking Door | Smoked Acrylic |
|-------------------------------|----------------|

| | |
|--------------------|-----|
| Vented Side Panels | Yes |
|--------------------|-----|

| | |
|--------------------------------|-----|
| Dual Vented Locking Rear Doors | Yes |
|--------------------------------|-----|

| | |
|-----------------------|-----|
| Reinforced Door Frame | Yes |
|-----------------------|-----|

| | |
|-------------------------|-----|
| Front & Rear Cage Rails | Yes |
|-------------------------|-----|

| | |
|------------------------------------|----------------|
| Dual Key Lock Sets (Doors & Sides) | 2 keys per set |
|------------------------------------|----------------|

| | |
|--------------|-------------|
| Cable Access | Top:Cutouts |
|--------------|-------------|

| | |
|--|---------------|
| | Bottom:Panels |
|--|---------------|

| | |
|--------------------------------------|-------|
| Electrostatic Powdercoat MicroFinish | Black |
|--------------------------------------|-------|

| | |
|------------------------------|---|
| Preinstalled 80CFM 110V Fans | 2 |
|------------------------------|---|

| | |
|---------|-----|
| Casters | Yes |
|---------|-----|

| | |
|---------------|-----|
| Leveling Feet | Yes |
|---------------|-----|

| | |
|----------------|-----|
| Ground Bus Bar | Yes |
|----------------|-----|

| | |
|----------------------|-----|
| Green Grounding Wire | Yes |
|----------------------|-----|

| | |
|-----------------------------|---------|
| Cage Nuts, Screws & Washers | 30 each |
|-----------------------------|---------|

| | |
|------------|----------|
| Compliance | EIA-310D |
|------------|----------|

| | |
|----------------|------------------------|
| Delivery Style | Assembled or Knockdown |
|----------------|------------------------|

SECTION

01



NEW SIZES

430 Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Rear Doors (AWG) | Front Door (AWG) | Base (AWG) |
|--------------|-------|----------------|-----------------|-------------------|-----------------|------------------|------------------|------------|
| FE4319-45-02 | Black | 45U | 16 | 18 | 18 | 18 | 18 | 16 |

FLOOR ENCLOSURES

430 SERIES – SMOKED ACRYLIC DOOR
27.5" X 36" SIZE GROUP



430 Smoked Acrylic Door Series

| Item No. ¹ | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) | Shipping Weight (Knockdown) ³ |
|-----------------------|--|-------------------------------|-------|-----|-------------------------------|-----|-----|-------------------------|--------------------------------|---|
| | | H | W | D | H | W | D | | | |
| FE4319-45-02 | 45U | 88" | 27.5" | 36" | 79" | 19" | 32" | 1400 | 288 | 253 |

1- To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.

2- Internal dimensions measure from front rails to back door. All 400 & 700 Series have an additional 2" usable space from rails to front door.

3- Knockdown Shipping Weight does not include weight of shipping pallet (approximately 60 lbs.)

SECTION


01

430 Dual Locking Rear Doors



These locking vented split doors allow mounting of enclosures in tighter spaces closer to the wall.

430 Removable Bottom Panels



Three removable panels for easy access to raised floors or for mounting equipment directly on the floor.

430 Adjustable Cage Nut Rails



Includes adjustable cage nut rails and cage nuts with standard #12-24 mounting screws. All cage nut rails are marked with an RU space index for easy alignment when mounting equipment.

430 Dual Pre-Installed Cooling Fans



Pre-Installed 110VAC 80CFM fan units keep equipment running cool.



SHIPPING OPTIONS

ASSEMBLED

UNASSEMBLED



Available to ship already assembled out-of-box, or ship unassembled in knockdown cartons for additional cost savings. To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.



FLOOR ENCLOSURES

700 SERIES – VENTED STEEL MESH DOOR
19" X 24" SIZE GROUP

SECTION

01



NEW SIZES

700 Vented Steel Mesh Front Door

700 Series

| | |
|--------------------------------------|-------------------------------------|
| External Rack Size Height | 69" (34U) 84" (42U) 88" (45U) |
| External Rack Size Width | 23" |
| External Rack Size Depth | 23" |
| Internal Mounting Format | 19" |
| Reversible Front Locking Door | Steel Mesh |
| Vented Side Panels | Yes |
| Dual Vented Locking Rear Doors | Yes |
| Reinforced Door Frame | Yes |
| Front & Rear Cage Rails | Yes |
| Dual Key Lock Sets (Doors & Sides) | 2 keys per set |
| Cable Access | Top:Cutouts Bottom:Panels |
| Electrostatic Powdercoat MicroFinish | Black |
| Preinstalled 80CFM 110V Fans | 2 |
| Casters | Yes |
| Leveling Feet | Yes |
| Ground Bus Bar | Yes |
| Green Grounding Wire | Yes |
| Cage Nuts, Screws & Washers | 30 each |
| Compliance | EIA-310D |
| Delivery Style | Assembled or Knockdown |

700 Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Rear Doors (AWG) | Front Door (AWG) | Base (AWG) |
|--------------|-------|----------------|-----------------|-------------------|-----------------|------------------|------------------|------------|
| FE7019-34-02 | Black | 34U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE7019-42-02 | Black | 42U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE7019-45-02 | Black | 45U | 16 | 18 | 18 | 18 | 18 | 16 |

FLOOR ENCLOSURES

700 SERIES – VENTED STEEL MESH DOOR

19" X 24" SIZE GROUP



700 Vented Steel Mesh Front Door Series

| Item No. ¹ | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) | Shipping Weight (Knockdown) ³ |
|-----------------------|--|----------------------------------|-----|-----|----------------------------------|-----|----------------|----------------------------|-----------------------------------|--|
| | | H | W | D | H | W | D ² | | | |
| FE7019-34-02 | 34U | 69" | 23" | 23" | 59.5" | 19" | 19.5" | 1400 | 197 | 164 |
| FE7019-42-02 | 42U | 84" | 23" | 23" | 74" | 19" | 19.5" | 1400 | 223 | 190 |
| FE7019-45-02 | 45U | 88" | 23" | 23" | 79" | 19" | 19.5" | 1400 | 229 | 196 |

1- To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.

2- Internal dimensions measure from front rails to back door. All 400 & 700 Series have an additional 2" usable space from rails to front door.

3- Knockdown Shipping Weight does not include weight of shipping pallet (approximately 60 lbs.)

SECTION


01

700 Dual Locking Rear Doors



These locking vented split doors allow mounting of enclosures in tighter spaces closer to the wall.

700 Removable Bottom Panels



Three removable panels for easy access to raised floors or for mounting equipment directly on the floor.

700 Adjustable Cage Nut Rails



Includes adjustable cage nut rails and cage nuts with standard #12-24 mounting screws. All cage nut rails are marked with an RU space index for easy alignment when mounting equipment.

700 Dual Pre-Installed Cooling Fans



Pre-Installed 110VAC 80CFM fan units keep equipment running cool.



SHIPPING OPTIONS

ASSEMBLED

UNASSEMBLED



Available to ship already assembled out-of-box, or ship unassembled in knockdown cartons for additional cost savings. To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.



FLOOR ENCLOSURES

710 SERIES – VENTED STEEL MESH DOOR
19" X 32" SIZE GROUP

SECTION

01



NEW SIZES

710 Vented Steel Mesh Front Door

710 Series

| | |
|--------------------------------------|-------------------------------------|
| External Rack Size Height | 69" (34U) 84" (42U) 88" (45U) |
| External Rack Size Width | 23" |
| External Rack Size Depth | 31" |
| Internal Mounting Format | 19" |
| Reversible Front Locking Door | Steel Mesh |
| Vented Side Panels | Yes |
| Dual Vented Locking Rear Doors | Yes |
| Reinforced Door Frame | Yes |
| Front & Rear Cage Rails | Yes |
| Dual Key Lock Sets (Doors & Sides) | 2 keys per set |
| Cable Access | Top:Cutouts Bottom:Panels |
| Electrostatic Powdercoat MicroFinish | Black |
| Preinstalled 80CFM 110V Fans | 2 |
| Casters | Yes |
| Leveling Feet | Yes |
| Ground Bus Bar | Yes |
| Green Grounding Wire | Yes |
| Cage Nuts, Screws & Washers | 30 each |
| Compliance | EIA-310D |
| Delivery Style | Assembled or Knockdown |

710 Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Rear Doors (AWG) | Front Door (AWG) | Base (AWG) |
|--------------|-------|----------------|-----------------|-------------------|-----------------|------------------|------------------|------------|
| FE7119-34-02 | Black | 34U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE7119-42-02 | Black | 42U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE7119-45-02 | Black | 45U | 16 | 18 | 18 | 18 | 18 | 16 |

FLOOR ENCLOSURES

710 SERIES – VENTED STEEL MESH DOOR

19" X 32" SIZE GROUP



710 Vented Steel Mesh Front Door Series

| Item No. ¹ | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) | Shipping Weight (Knockdown) ³ |
|-----------------------|--|----------------------------------|-----|-----|----------------------------------|-----|----------------|----------------------------|-----------------------------------|--|
| | | H | W | D | H | W | D ² | | | |
| FE7119-34-02 | 34U | 69" | 23" | 31" | 59.5" | 19" | 27.5" | 1400 | 216 | 183 |
| FE7119-42-02 | 42U | 84" | 23" | 31" | 74" | 19" | 27.5" | 1400 | 247 | 214 |
| FE7119-45-02 | 45U | 88" | 23" | 31" | 79" | 19" | 27.5" | 1400 | 253 | 220 |

1- To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.

2- Internal dimensions measure from front rails to back door. All 400 & 700 Series have an additional 2" usable space from rails to front door.

3- Knockdown Shipping Weight does not include weight of shipping pallet (approximately 60 lbs.)

SECTION


01

710 Dual Locking Rear Doors



These locking vented split doors allow mounting of enclosures in tighter spaces closer to the wall.

710 Removable Bottom Panels



Three removable panels for easy access to raised floors or for mounting equipment directly on the floor.

710 Adjustable Cage Nut Rails



Includes adjustable cage nut rails and cage nuts with standard #12-24 mounting screws. All cage nut rails are marked with an RU space index for easy alignment when mounting equipment.

710 Dual Pre-Installed Cooling Fans



Pre-Installed 110VAC 80CFM fan units keep equipment running cool.



SHIPPING OPTIONS

ASSEMBLED

UNASSEMBLED



Available to ship already assembled out-of-box, or ship unassembled in knockdown cartons for additional cost savings. To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.



FLOOR ENCLOSURES

720 SERIES – VENTED STEEL MESH DOOR
27.5" X 32" SIZE GROUP

SECTION

01



NEW SIZES

720 Vented Steel Mesh Front Door

720 Series

| | |
|--------------------------------------|------------------------------|
| External Rack Size Height | 84" (42U) 88" (45U) |
| External Rack Size Width | 27" |
| External Rack Size Depth | 31" |
| Internal Mounting Format | 19" |
| Reversible Front Locking Door | Steel Mesh |
| Vented Side Panels | Yes |
| Dual Vented Locking Rear Doors | Yes |
| Reinforced Door Frame | Yes |
| Front & Rear Cage Rails | Yes |
| Dual Key Lock Sets (Doors & Sides) | 2 keys per set |
| Cable Access | Top:Cutouts Bottom:Panels |
| Electrostatic Powdercoat MicroFinish | Black |
| Preinstalled 80CFM 110V Fans | 2 |
| Casters | Yes |
| Leveling Feet | Yes |
| Ground Bus Bar | Yes |
| Green Grounding Wire | Yes |
| Cage Nuts, Screws & Washers | 30 each |
| Compliance | EIA-310D |
| Delivery Style | Assembled or Knockdown |

720 Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Rear Doors (AWG) | Front Door (AWG) | Base (AWG) |
|--------------|-------|----------------|-----------------|-------------------|-----------------|------------------|------------------|------------|
| FE7219-42-02 | Black | 42U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE7219-45-02 | Black | 45U | 16 | 18 | 18 | 18 | 18 | 16 |

FLOOR ENCLOSURES

720 SERIES – VENTED STEEL MESH DOOR

27.5" X 32" SIZE GROUP



720 Vented Steel Mesh Front Door Series

| Item No. ¹ | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) | Shipping Weight (Knockdown) ³ |
|-----------------------|--|----------------------------------|-----|-----|----------------------------------|-----|----------------|----------------------------|-----------------------------------|--|
| | | H | W | D | H | W | D ² | | | |
| FE7219-42-02 | 42U | 84" | 27" | 31" | 74" | 19" | 27.5" | 1400 | 264 | 229 |
| FE7219-45-02 | 45U | 88" | 27" | 31" | 79" | 19" | 27.5" | 1400 | 277 | 242 |

1- To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.

2- Internal dimensions measure from front rails to back door. All 400 & 700 Series have an additional 2" usable space from rails to front door.

3- Knockdown Shipping Weight does not include weight of shipping pallet (approximately 60 lbs.)

SECTION


01

720 Dual Locking Rear Doors



These locking vented split doors allow mounting of enclosures in tighter spaces closer to the wall.

720 Removable Bottom Panels



Three removable panels for easy access to raised floors or for mounting equipment directly on the floor.

720 Adjustable Cage Nut Rails



Includes adjustable cage nut rails and cage nuts with standard #12-24 mounting screws. All cage nut rails are marked with an RU space index for easy alignment when mounting equipment.

720 Dual Pre-Installed Cooling Fans



Pre-Installed 110VAC 80CFM fan units keep equipment running cool.



SHIPPING OPTIONS

ASSEMBLED

UNASSEMBLED



Available to ship already assembled out-of-box, or ship unassembled in knockdown cartons for additional cost savings. To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.



FLOOR ENCLOSURES

730 SERIES – VENTED STEEL MESH DOOR
27.5" X 36" SIZE GROUP

SECTION

01



NEW SIZES

730 Vented Steel Mesh Front Door

730 Series

| | |
|--------------------------------------|------------------------------|
| External Rack Size Height | 84" (42U) 88" (45U) |
| External Rack Size Width | 27.5" |
| External Rack Size Depth | 36" |
| Internal Mounting Format | 19" |
| Reversible Front Locking Door | Steel Mesh |
| Vented Side Panels | Yes |
| Dual Vented Locking Rear Doors | Yes |
| Reinforced Door Frame | Yes |
| Front & Rear Cage Rails | Yes |
| Dual Key Lock Sets (Doors & Sides) | 2 keys per set |
| Cable Access | Top:Cutouts Bottom:Panels |
| Electrostatic Powdercoat MicroFinish | Black |
| Preinstalled 80CFM 110V Fans | 2 |
| Casters | Yes |
| Leveling Feet | Yes |
| Ground Bus Bar | Yes |
| Green Grounding Wire | Yes |
| Cage Nuts, Screws & Washers | 30 each |
| Compliance | EIA-310D |
| Delivery Style | Assembled or Knockdown |

730 Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Rear Doors (AWG) | Front Door (AWG) | Base (AWG) |
|--------------|-------|----------------|-----------------|-------------------|-----------------|------------------|------------------|------------|
| FE7319-42-02 | Black | 42U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE7319-45-02 | Black | 45U | 16 | 18 | 18 | 18 | 18 | 16 |

FLOOR ENCLOSURES

730 SERIES – VENTED STEEL MESH DOOR

27.5" X 36" SIZE GROUP



730 Vented Steel Mesh Front Door Series

| Item No. ¹ | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) | Shipping Weight (Knockdown) ³ |
|-----------------------|--|----------------------------------|-------|-----|----------------------------------|-----|----------------|----------------------------|-----------------------------------|--|
| | | H | W | D | H | W | D ² | | | |
| FE7319-42-02 | 42U | 84" | 27.5" | 36" | 74" | 19" | 32" | 1400 | 302 | 260 |
| FE7319-45-02 | 45U | 88" | 27.5" | 36" | 79" | 19" | 32" | 1400 | 308 | 273 |

1- To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.

2- Internal dimensions measure from front rails to back door. All 400 & 700 Series have an additional 2" usable space from rails to front door.

3- Knockdown Shipping Weight does not include weight of shipping pallet (approximately 60 lbs.)

SECTION

01

730 Dual Locking Rear Doors



These locking vented split doors allow mounting of enclosures in tighter spaces closer to the wall.

730 Removable Bottom Panels



Three removable panels for easy access to raised floors or for mounting equipment directly on the floor.

730 Adjustable Cage Nut Rails



Includes adjustable cage nut rails and cage nuts with standard #12-24 mounting screws. All cage nut rails are marked with an RU space index for easy alignment when mounting equipment.

730 Dual Pre-Installed Cooling Fans



Pre-Installed 110VAC 80CFM fan units keep equipment running cool.



SHIPPING OPTIONS

ASSEMBLED

UNASSEMBLED



Available to ship already assembled out-of-box, or ship unassembled in knockdown cartons for additional cost savings. To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.



FLOOR ENCLOSURES

740 SERIES – VENTED STEEL MESH DOOR
27.5" X 42" SIZE GROUP

SECTION

01



NEW SIZES

740 Vented Steel Mesh Front Door

740 Series

| | |
|--------------------------------------|--|
| External Rack Size Height | 59" (28U) 69" (34U) 84" (42U) 88" (45U) |
| External Rack Size Width | 27" |
| External Rack Size Depth | 41.7" |
| Internal Mounting Format | 19" |
| Reversible Front Locking Door | Steel Mesh |
| Vented Side Panels | Yes |
| Dual Vented Locking Rear Doors | Yes |
| Reinforced Door Frame | Yes |
| Front & Rear Cage Rails | Yes |
| Dual Key Lock Sets (Doors & Sides) | 2 keys per set |
| Cable Access | Top:Cutouts Bottom:Panels |
| Electrostatic Powdercoat MicroFinish | Black |
| Preinstalled 80CFM 110V Fans | 2 |
| Casters | Yes |
| Leveling Feet | Yes |
| Ground Bus Bar | Yes |
| Green Grounding Wire | Yes |
| Cage Nuts, Screws & Washers | 30 each |
| Compliance | EIA-310D |
| Delivery Style | Assembled or Knockdown |

740 Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Rear Doors (AWG) | Front Door (AWG) | Base (AWG) |
|--------------|-------|----------------|-----------------|-------------------|-----------------|------------------|------------------|------------|
| FE7419-28-02 | Black | 28U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE7419-34-02 | Black | 34U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE7419-42-02 | Black | 42U | 16 | 18 | 18 | 18 | 18 | 16 |
| FE7419-45-02 | Black | 45U | 16 | 18 | 18 | 18 | 18 | 16 |

FLOOR ENCLOSURES

740 SERIES – VENTED STEEL MESH DOOR

27.5" X 42" SIZE GROUP



740 Vented Steel Mesh Front Door

| Item No. ¹ | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) | Shipping Weight (Knockdown) ³ |
|-----------------------|--|----------------------------------|-----|-----|----------------------------------|-----|----------------|----------------------------|-----------------------------------|--|
| | | H | W | D | H | W | D ² | | | |
| FE7419-28-02 | 28U | 59" | 27" | 42" | 49" | 19" | 37.5" | 1900 | 306 | 271 |
| FE7419-34-02 | 34U | 69" | 27" | 42" | 59" | 19" | 37.5" | 1900 | 314 | 279 |
| FE7419-42-02 | 42U | 84" | 27" | 42" | 74" | 19" | 37.5" | 2000 | 322 | 287 |
| FE7419-45-02 | 45U | 88" | 27" | 42" | 79" | 19" | 37.5" | 2000 | 330 | 295 |

1- To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.

2- Internal dimensions measure from front rails to back door. All 400 & 700 Series have an additional 2" usable space from rails to front door.

3- Knockdown Shipping Weight does not include weight of shipping pallet (approximately 60 lbs.)

SECTION


01

740 Dual Locking Rear Doors



These locking vented split doors allow mounting of enclosures in tighter spaces closer to the wall.

740 Removable Bottom Panels



Three removable panels for easy access to raised floors or for mounting equipment directly on the floor.

740 Adjustable Cage Nut Rails



Includes adjustable cage nut rails and cage nuts with standard #12-24 mounting screws. All cage nut rails are marked with an RU space index for easy alignment when mounting equipment.

740 Dual Pre-Installed Cooling Fans



Pre-Installed 110VAC 80CFM fan units keep equipment running cool.



SHIPPING OPTIONS

ASSEMBLED

UNASSEMBLED



Available to ship already assembled out-of-box, or ship unassembled in knockdown cartons for additional cost savings. To obtain a knockdown version Floor Enclosure, add a 'K' to the end of the part number.



FLOOR ENCLOSURES

HOME THEATER ENCLOSURES

23" x 24" SIZE GROUP

SECTION

01



HT Home Theater Enclosure

| | HT Series 3ft. | 5ft. |
|--------------------------------------|----------------|--------------|
| External Rack Size Height | 36" (16U) | 61" (30U) |
| External Rack Size Width | 22.5" | 22.5" |
| External Rack Size Depth | 24" | 24" |
| Internal Mounting Format | 19" | 19" |
| Pre-Installed Vented Shelves (2U) | 3 | 4 |
| Pre-Installed Vented Shelves (5U) | 0 | 1 |
| Shelf Clamps | 3 | 5 |
| Vented Spacers (2U) | 3 | 5 |
| Cable Organizer Bars | 3 | 5 |
| Front and Rear Door | N/A | N/A |
| Removable Vented Side Panels | Yes | Yes |
| Threaded Mounting Rails (#12-24) | Yes | Yes |
| Cable Access | Front & Rear | Front & Rear |
| Electrostatic Powdercoat MicroFinish | Black | Black |
| Preinstalled 80CFM 110V Fans | 0 | 0 |
| Soft White Locking Rubber Casters | Yes | Yes |
| Removable Stainless Steel Handles | Yes | Yes |
| Compliance | EIA-310D | EIA-310D |
| Delivery Style | Assembled | Assembled |

HT Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Base (AWG) |
|--------------|-------|----------------|-----------------|-------------------|-----------------|------------|
| HT6019-16-02 | Black | 16U | 16 | 18 | 18 | 16 |
| HT6019-30-02 | Black | 30U | 16 | 18 | 18 | 16 |

FLOOR ENCLOSURES

HOME THEATER ENCLOSURES

23" x 24" SIZE GROUP



HT Home Theater Enclosure Series

| Item No. ¹ | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) | Shipping Weight (Knockdown) ³ |
|-----------------------|--|----------------------------------|-------|-----|----------------------------------|-----|----------------|----------------------------|-----------------------------------|--|
| | | H | W | D | H | W | D ² | | | |
| HT6019-16-02 | 16U | 36" | 22.5" | 24" | 28" | 18" | 19" | 600 | 106 | N/A |
| HT6019-30-02 | 30U | 61" | 22.5" | 24" | 52.5" | 18" | 22" | 670 | 167 | N/A |

1- Home Theater Floor Enclosures are not available in a knockdown version.

2- Internal dimensions measure from front rails to back door. All HT Series have an additional 3" usable space from rails to front door.

3- Knockdown Shipping Weight does not include weight of shipping pallet (approximately 60 lbs.)

SECTION

01

HT Removable Vented Side Panels



Comes complete with vented removable side panels for easy access to equipment.

HT Pre-Installed Shelving




Pre-Installed shelving for out-of-the-box installation. Each shelf includes a screw-down shelf clamp to hold the A/V equipment in place and cable organizer bar.

HT Fixed Threaded Mounting Rails



Designed with front & rear mounting rails which are threaded for standard #12-24 mounting screws.

HT Locking Soft White Casters



Constructed with locking soft white casters for scuffless moving of equipment.

HT Stainless Steel Push-Pull Handles



Stainless steel push-pull handles makes it easy to gain access to rear equipment wiring.





WALL MOUNT ENCLOSURES

SECTION

02

200 SERIES
w/ Removable Side Panels

210 SERIES
Honeycomb Meshed Steel

300 SERIES
w/ Swing Out Design

600 SERIES – EZ ASSEMBLY
w/ Fixed Sided Panels

DVR/NVR Security Enclosures



WALL MOUNT ENCLOSURES

200 Removable Side Panel Series Page No.

200 Series 25-26

210 Honeycomb Meshed Steel Page No.

210 Series *Honeycomb*
VENTED WALL MOUNT
ENCLOSURES  27-28

300 Swing-Out Design Series Page No.

300 Series 29-30

600 EZ-Assembly Series Page No.

600 Series 31-32

DVR DVR / NVR Security Enclosures Page No.

DVR / NVR Series 33-34

SECTION

02



WALL MOUNT ENCLOSURES

200 SERIES REMOVABLE SIDE PANELS

NEW EXTENDED DEPTH SIZES

SECTION

02



200 Removable Side Panel Series

| 200 Series | Standard Depth Version | Extended Depth Version |
|--------------------------------------|-------------------------------------|-------------------------------|
| External Rack Size Height | 5U 7U 9U 11U 14U 16U | 9U 11U 20U 28U |
| External Rack Size Width | 21" | 21" |
| External Rack Size Depth | 20" | 28" |
| Mounting Format (Internal) | 19" | 19" |
| Reversible Front Locking Door | Smoked Acrylic | Smoked Acrylic |
| Vented Side Panels | Removable | Removable |
| Hinged Swing Out Design | No | No |
| Reinforced Door Frame | Yes | Yes |
| Front Cage Rails | Yes | Yes |
| Single Key Lock Set | 2 keys per set | 2 keys per set |
| Cable Access | Top:Cutouts Bottom:Cutouts | Top:Cutouts Bottom:Cutouts |
| Electrostatic Powdercoat MicroFinish | Black | Black |
| Preinstalled 80CFM 110V Fans | 1 | 1 |
| Cage Nuts, Screws & Washers | 12 Each | 12 Each |
| Compliance | EIA-310D | EIA-310D |
| Delivery Style | Assembled | Assembled |

200 Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Base (AWG) |
|----------------|-------|----------------|-----------------|-------------------|-----------------|------------|
| WM2019-05-02 | Black | 5U | 18 | 18 | 18 | 18 |
| WM2019-07-02 | Black | 7U | 18 | 18 | 18 | 18 |
| WM2019-09-02 | Black | 9U | 18 | 18 | 18 | 18 |
| WM2019-09-02D | Black | 9U | 18 | 18 | 18 | 18 |
| WM2019-11-02 | Black | 11U | 18 | 18 | 18 | 18 |
| WM2019-11-02D | Black | 11U | 18 | 18 | 18 | 18 |
| WM2019-14-02 | Black | 14U | 18 | 18 | 18 | 18 |
| WM2019-16-02 | Black | 16U | 18 | 18 | 18 | 18 |
| WM 2019-20-02D | Black | 20U | 18 | 18 | 18 | 18 |
| WM 2019-28-02D | Black | 28U | 18 | 18 | 18 | 18 |

WALL MOUNT ENCLOSURES

200 SERIES REMOVABLE SIDE PANELS



200 Removable Side Panel Series

| Item No. | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) |
|----------------|--|----------------------------------|-----|-----|----------------------------------|-----|----------------|----------------------------|-----------------------------------|
| | | H | W | D | H | W | D ¹ | | |
| WM2019-05-02 | 5U | 12.5" | 21" | 20" | 9.5" | 19" | 16" | 130 | 39 |
| WM2019-07-02 | 7U | 16" | 21" | 20" | 12.5" | 19" | 16" | 130 | 43 |
| WM2019-09-02 | 9U | 19.5" | 21" | 20" | 16" | 19" | 16" | 130 | 48 |
| WM2019-09-02D | 9U | 19.5" | 21" | 28" | 16" | 19" | 24" | 130 | 57 |
| WM2019-11-02 | 11U | 23" | 21" | 20" | 19.5" | 19" | 16" | 130 | 52 |
| WM2019-11-02D | 11U | 23" | 21" | 28" | 19.5" | 19" | 24" | 130 | 61 |
| WM2019-14-02 | 14U | 28" | 21" | 20" | 24.5" | 19" | 16" | 130 | 66 |
| WM2019-16-02 | 16U | 31.5" | 21" | 20" | 28" | 19" | 16" | 130 | 70 |
| WM 2019-20-02D | 20U | 38.5" | 21" | 28" | 35" | 19" | 24" | 130 | 100 |
| WM 2019-28-02D | 28U | 52.5" | 21" | 28" | 49" | 19" | 24" | 130 | 125 |

SECTION

02

1- Internal dimensions measure from front rails to back. All Wall Mount Enclosures have an additional 2" usable space from rails to front door.

200 Reversible Locking Front Door



Front locking door is reversible for left or right side opening.

200 Vented Removable Side Panels



Vented removable side panels with key lock for secure and easy access.



200 Adjustable Cage Nut Rails



Includes adjustable cage nut rails and cage nuts with standard #12-24 mounting screws. All cage nut rails are marked with an RU space index for easy alignment when mounting equipment.

200 Pre-Installed Cooling Fans



Pre-Installed 110VAC 80CFM fan units keep equipment running cool.

200 Ships Fully Assembled



All 5U to 11U sizes are UPS shippable and ready for out-of-the-box installation.



WALL MOUNT ENCLOSURES

210 SERIES - HONEYCOMB VENTED MESHED STEEL REMOVABLE SIDE PANELS

210
SERIES
Honeycomb
VENTED WALL MOUNT
ENCLOSURES

SECTION

02

SUPERIOR VENTILATION & COOLING

SECURE, LOCKING STRUCTURE

3 SIDES EASY ACCESS



210 Honeycomb Meshed Steel

210 Series

| | |
|--------------------------------------|-------------------------------------|
| External Rack Size Height | 16" (7U) 19.5" (9U) 23" (11U) |
| External Rack Size Width | 20.5" |
| External Rack Size Depth | 20" |
| Mounting Format (Internal) | 19" |
| Reversible Front Locking Door | Meshed Steel |
| Vented Side Panels | Removable |
| Hinged Swing Out Design | No |
| Reinforced Door Frame | Yes |
| Front & Rear Cage Rails | Yes |
| Key Lock Set | 2 keys per set |
| Cable Access | Top:Cutouts Bottom:Cutouts |
| Electrostatic Powdercoat MicroFinish | Black |
| Preinstalled 80CFM 110V Fans | 1 |
| Cage Nuts, Screws & Washers | 12 Each |
| Compliance | EIA-310D |
| Delivery Style | Assembled |

210 Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Base (AWG) |
|--------------|-------|----------------|-----------------|-------------------|-----------------|------------|
| WM2119-07-02 | Black | 7U | 18 | 18 | 18 | 18 |
| WM2119-09-02 | Black | 9U | 18 | 18 | 18 | 18 |
| WM2119-11-02 | Black | 11U | 18 | 18 | 18 | 18 |

WALL MOUNT ENCLOSURES



210 SERIES - HONEYCOMB VENTED MESHED STEEL REMOVABLE SIDE PANELS

210 Honeycomb Meshed Steel

| Item No. | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) |
|--------------|--|----------------------------------|-----|-----|----------------------------------|-----|----------------|----------------------------|-----------------------------------|
| | | H | W | D | H | W | D ¹ | | |
| WM2119-07-02 | 7U | 16" | 21" | 20" | 12.5" | 19" | 16" | 130 | 35 |
| WM2119-09-02 | 9U | 19.5" | 21" | 20" | 16" | 19" | 16" | 130 | 43 |
| WM2119-11-02 | 11U | 23" | 21" | 20" | 19.5" | 19" | 16" | 130 | 47 |

1 - Internal dimensions measure from front rails to back.
All Wall Mount Enclosures have an additional 2" usable space from rails to front door.

SECTION 02

210 Reversible Locking Front Door



Front locking door is reversible for left or right side opening.

210 3-Sides Vented Meshed Steel



Vented fixed side panels for better air flow and equipment cooling.

210 Adjustable Cage Nut Rails



Includes adjustable cage nut rails and cage nuts with standard #12-24 mounting screws. All cage nut rails are marked with an RU space index for easy alignment when mounting equipment.

210 Pre-Installed Cooling Fan





Pre-Installed 110VAC 80CFM fan units keep equipment running cool.

210 Ships Fully Assembled



All sizes are UPS shippable and ready for out-of-the-box installation.



SUPERIOR VENTILATION & COOLING



SECURE, LOCKING STRUCTURE



3 SIDES EASY ACCESS



WALL MOUNT ENCLOSURES

300 SERIES

SWING-OUT W/FIXED SIDE PANELS

NEW EXTENDED DEPTH SIZES

SECTION

02



300 Swing-Out Design Series

| 300 Series | Standard Depth Version | Extended Depth Version |
|--------------------------------------|-------------------------------|--------------------------------|
| External Rack Size Height | 7U 9U 11U 14U 16U | 9U 16U 20U 24U 28U |
| External Rack Size Width | 20.5" | 20.5" |
| External Rack Size Depth | 23.5" | 30.5" |
| Mounting Format (Internal) | 19" | 19" |
| Reversible Front Locking Door | Smoked Acrylic | Smoked Acrylic |
| Vented Side Panels | Fixed | Fixed |
| Hinged Swing Out Design | Yes | Yes |
| Reinforced Door Frame | Yes | Yes |
| Front Cage Rails | Yes | Yes |
| Single Key Lock Set | 2 keys per set | 2 keys per set |
| Cable Access | Top:Cutouts Bottom:Cutouts | Top:Cutouts Bottom:Cutouts |
| Electrostatic Powdercoat MicroFinish | Black | Black |
| Preinstalled 80CFM 110V Fans | 1 | 1 |
| Cage Nuts, Screws & Washers | 12 Each | 12 Each |
| Compliance | EIA-310D | EIA-310D |
| Delivery Style | Assembled | Assembled |

300 Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Base (AWG) |
|----------------|-------|----------------|-----------------|-------------------|-----------------|------------|
| WM3019-07-02 | Black | 7U | 18 | 18 | 18 | 18 |
| WM3019-09-02 | Black | 9U | 18 | 18 | 18 | 18 |
| WM3019-09-02D | Black | 9U | 18 | 18 | 18 | 18 |
| WM3019-11-02 | Black | 11U | 18 | 18 | 18 | 18 |
| WM3019-14-02 | Black | 14U | 18 | 18 | 18 | 18 |
| WM3019-16-02 | Black | 16U | 18 | 18 | 18 | 18 |
| WM3019-16-02D | Black | 16U | 18 | 18 | 18 | 18 |
| WM 3019-20-02D | Black | 20U | 18 | 18 | 18 | 18 |
| WM 3019-24-02D | Black | 24U | 18 | 18 | 18 | 18 |
| WM 3019-28-02D | Black | 28U | 18 | 18 | 18 | 18 |

WALL MOUNT ENCLOSURES

300 SERIES

SWING-OUT W/FIXED SIDE PANELS



300 Swing-Out Design Series

| Item No. | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) |
|----------------|--|----------------------------------|-------|-------|----------------------------------|-----|-----|----------------------------|-----------------------------------|
| | | H | W | D | H | W | D' | | |
| WM3019-07-02 | 7U | 15" | 20.5" | 23.5" | 12.5" | 19" | 17" | 130 | 48 |
| WM3019-09-02 | 9U | 18.5" | 20.5" | 23.5" | 16" | 19" | 17" | 130 | 50 |
| WM3019-09-02D | 9U | 18.5" | 20.5" | 30.5" | 16" | 19" | 24" | 130 | 55 |
| WM3019-11-02 | 11U | 22" | 20.5" | 23.5" | 19.5" | 19" | 17" | 130 | 54 |
| WM3019-14-02 | 14U | 27" | 20.5" | 23.5" | 24.5" | 19" | 17" | 130 | 72 |
| WM3019-16-02 | 16U | 30.5" | 20.5" | 23.5" | 28" | 19" | 17" | 130 | 82 |
| WM3019-16-02D | 16U | 30.5" | 20.5" | 30.5" | 28" | 19" | 24" | 130 | 88 |
| WM 3019-20-02D | 20U | 37.5" | 20.5" | 30.5" | 35" | 19" | 24" | 130 | 106 |
| WM 3019-24-02D | 24U | 44.5" | 20.5" | 30.5" | 42" | 19" | 24" | 130 | 120 |
| WM 3019-28-02D | 28U | 51.5" | 20.5" | 30.5" | 49" | 19" | 24" | 130 | 138 |

SECTION

02

1- Internal dimensions measure from front rails to back door. All Wall Mount Enclosures have an additional 2" of usable space from rails to front door and all 300 Series Wall Mount Enclosures have an additional 3" of usable space in the hinged rear door.

300 Reversible Locking Front Door



Front locking door is reversible for left or right side opening.

300 Vented Fixed Side Panels



Vented fixed side panels for better air flow and equipment cooling.

300 Adjustable Cage Nut Rails



Includes adjustable cage nut rails and cage nuts with standard #12-24 mounting screws. All cage nut rails are marked with an RU space index for easy alignment when mounting equipment.

300 Pre-Installed Cooling Fans



Pre-Installed 110VAC 80CFM fan units keep equipment running cool.

300 Swing-Out Locking Design




Swing-Out feature allows easy access to back of equipment with key lock to prevent tampering.

300 Ships Fully Assembled



All 5U to 11U sizes are UPS shippable and ready for out-of-the-box installation.





WALL MOUNT ENCLOSURES

600 SERIES

EZ-ASSEMBLY W/FIXED SIDE PANELS

SECTION 02

**10-Minute
Assembly**



600 EZ-Assembly Series

600 Series

| | |
|--------------------------------------|-----------------------------------|
| External Rack Size Height | 15" (7U) 18" (9U) 22" (11U) |
| External Rack Size Width | 20.5" |
| External Rack Size Depth | 20" |
| Mounting Format (Internal) | 19" |
| Reversible Front Locking Door | Smoked Acrylic |
| Vented Side Panels | Fixed |
| Hinged Swing Out Design | No |
| Reinforced Door Frame | Yes |
| Front Cage Rails | Yes |
| Single Key Lock Set | 2 keys per set |
| Cable Access | Top:Cutouts Bottom:Cutouts |
| Electrostatic Powdercoat MicroFinish | Black |
| Preinstalled 80CFM 110V Fans | 1 |
| Cage Nuts, Screws & Washers | 12 Each |
| Compliance | EIA-310D |
| Delivery Style | Knockdown |

600 Structure and Fabrication

| Item No. | Color | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Base (AWG) |
|------------|-------|----------------|-----------------|-------------------|-----------------|------------|
| EZ19-07-02 | Black | 7U | 18 | 18 | 18 | 18 |
| EZ19-09-02 | Black | 9U | 18 | 18 | 18 | 18 |
| EZ19-11-02 | Black | 11U | 18 | 18 | 18 | 18 |

EZ-Assembly Instructions




1 Install top and bottom panels by tightening the nuts on the rear panel.



2 Pre-position for desired equipment depth and install left and right rails.



3 Install the left and right panels with the supplied mounting screws.



4 Install the front door by aligning with the corresponding side panel; right or left hand opening.

WALL MOUNT ENCLOSURES



600 SERIES

EZ-ASSEMBLY W/FIXED SIDE PANELS

600 EZ-Assembly Series

| Item No. | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Knockdown) |
|------------|--|----------------------------------|-------|-----|----------------------------------|-----|----------------|----------------------------|-----------------------------------|
| | | H | W | D | H | W | D ¹ | | |
| EZ19-07-02 | 7U | 15" | 20.5" | 20" | 12.5" | 19" | 18" | 130 | 36 |
| EZ19-09-02 | 9U | 18" | 20.5" | 20" | 16" | 19" | 18" | 130 | 41 |
| EZ19-11-02 | 11U | 22" | 20.5" | 20" | 19.5" | 19" | 18" | 130 | 50 |

1- Internal dimensions measure from front rails to back. All Wall Mount Enclosures have an additional 2" usable space from rails to front door.

SECTION

02

600 Reversible Locking Front Door



Front locking door is reversible for left or right side opening.

600 Vented Fixed Side Panels



Vented fixed side panels for better air flow and equipment cooling.

600 Adjustable Cage Nut Rails



Includes adjustable cage nut rails and cage nuts with standard #12-24 mounting screws. All cage nut rails are marked with an RU space index for easy alignment when mounting equipment.

600 Pre-Installed Cooling Fan



Pre-Installed 110VAC 80CFM fan units keep equipment running cool.

600 Ships in Knockdown Box



All sizes are UPS shippable and are able to be assembled in less than 10 minutes.





DVR/NVR SECURITY ENCLOSURES

DVR / NVR SERIES

SECTION
02

Clear Acrylic Door



Solid Steel Door

DVR Security Enclosure Series

DVR Series

| | |
|--------------------------------------|------------------------------|
| External Rack Size Height | 9" 1(U) |
| External Rack Size Width | 20" |
| External Rack Size Depth | 21" |
| Mounting Format (Internal) | 19" |
| Hinged Front Locking Door | Solid Metal or Clear Acrylic |
| Reinforced Door Frame | Yes |
| Rear Cage Mounts | Yes |
| Single Key Lock Set | 2 keys per set |
| Cable Access | Rear: Cutouts |
| Electrostatic Powdercoat MicroFinish | Black |
| Preinstalled 80CFM 110V Fans | 1 |
| Cage Nuts, Screws & Washers | 2 each |
| Compliance | EIA-310D |
| Delivery Style | Assembled |

DVR Structure and Fabrication

| Item No. | Color | Door Structure | Rack Units (U) | Structure (AWG) | Side Panels (AWG) | Top Panel (AWG) | Base (AWG) |
|---------------|-------|---------------------------------|----------------|-----------------|-------------------|-----------------|------------|
| SE0920-21-02 | Black | Solid Metal | 1U | 18 | 18 | 18 | 18 |
| SE0920-21-02A | Black | Metal Frame with Acrylic Window | 1U | 18 | 18 | 18 | 18 |

DVR/NVR SECURITY ENCLOSURES

DVR / NVR SERIES



DVR Security Enclosure Series

| Item No. | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) |
|-------------------------------|--|-------------------------------|-----|-----|-------------------------------|-----|----------------|-------------------------|--------------------------------|
| | | H | W | D | H | W | D ¹ | | |
| SE0920-21-02 SE0920-21-02A | 1U | 9" | 20" | 21" | 8" | 19" | 20" | 130 | 27 |

1- Internal dimensions measure from front door to rear.

SECTION 02

DVR Removable Top Panel



Top panel is removable for easy access to equipment and wiring.

DVR Hinged Locking Front Door



Hinged front door is available in see-through acrylic or solid metal with key lock for secure and easy access.

DVR Fixed Cage Nut Mount



1U fixed cage nut mount for cage nuts threaded for standard #12-24 mounting screws.

DVR Pre-Installed Cooling Fan



Pre-Installed 110VAC 80CFM fan unit keeps equipment running cool.



Recommended Accessories

DVR Wall Mount Brackets (#WB-SE-02)

Optional wall mount brackets allow flexibility of tabletop or wall mount installations.

WB-SE-02



DVR 12 Outlet AC Power Strip (#HPS-E12P)

Optional 1U 120VAC/12A EMI/RFI surge strip for powering DVR or other AC devices.

HPS-E12P





OPEN FRAME RACKS

SECTION


03

4-POST FLOOR RACKS
Adjustable

2-POST FLOOR RACKS
Aluminum & Steel

WALL MOUNT RACKS
Fixed & Swing-Out

WALL MOUNT BRACKETS
Hinged & Non-Hinged





OPEN FRAME RACKS

4PR 4-Post Open Frame Racks **Page No.**

4PR Series Adjustable **37-38**

2PR 2-Post Open Frame Racks **Page No.**

2PR Series Aluminum & Steel **39-40**

WMR Wall Mount Open Frame Racks **Page No.**

WMR Series Adjustable, Fixed & Swing-Out **41**

WMB Wall Mount Brackets **Page No.**

WMB Series Hinged & Non-Hinged **42**

NEW BRACKET DESIGN

SECTION
03



OPEN FRAME FLOOR RACKS

4-POST
ADJUSTABLE

SECTION
03



4PR 4-Post Open Frame Racks

| | 4PR SERIES 4FT. | 7FT. |
|--------------------------------------|------------------------|--------------------|
| Item No. | FR1924-28-02 | FR1924-45-02 |
| Rack Size Height (Rack Units) | 54" (28U) | 84" (45U) |
| Rack Size Width | 21" | 21" |
| Rack Size Depth | Adjustable 24"-36" | Adjustable 24"-36" |
| Mounting Format | 19" | 19" |
| Load Capacity | 1000lbs | 1700lbs |
| Dual Mounting Rails | Cage Nut (#12-24) | Cage Nut (#12-24) |
| Numbered RU positions | Yes | Yes |
| Electrostatic Powdercoat MicroFinish | Black | Black |
| Cage Nuts, Screws & Washers | 20 each | 40 each |
| Cable Management D-Rings (Plastic) | 16 | 32 |
| Base Design | Floor Mount | Floor Mount |
| Compliance | EIA-310D | EIA-310D |
| Delivery Style | Knockdown | Knockdown |

**Cable Management
D-Rings Included**



4PR Structure and Fabrication

| Item No. | Color | Rack Units (U) | Material | Posts | Top Brackets (AWG) | Base (AWG) |
|--------------|-------|----------------|-------------------|-------|--------------------|------------|
| FR1924-28-02 | Black | 28U | Cold Rolled Steel | 4 | 14 | 10 |
| FR1924-45-02 | Black | 45U | Cold Rolled Steel | 4 | 14 | 10 |

OPEN FRAME FLOOR RACKS

4-POST
ADJUSTABLE



4PR 4-Post Open Frame Racks

| Item No. | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Knockdown) |
|--------------|--|----------------------------------|-----|---------|----------------------------------|-----|---------|----------------------------|-----------------------------------|
| | | H | W | D | H | W | D | | |
| FR1924-28-02 | 28U | 54" | 21" | 24"-36" | 49" | 19" | 24"-36" | 1000 | 53 |
| FR1924-45-02 | 45U | 84" | 21" | 24"-36" | 79" | 19" | 24"-36" | 1700 | 66 |

SECTION
03

4PR Adjustable Depth



Pre-drilled adjustable depths are:
24", 26.5", 29", 31.5, 34, 36".

4PR Floor Mount Holes



Constructed with mounting holes for
mounting securely to floor.

4PR Dual-Sided Rails



"U" shaped cage nut rail design to allow
front and rear mounting of equipment.

4PR Angled Top Braces



Reinforced angled top brace supports
provide added load strength.

4PR Rack Unit Numbered Rails



Numbered rack units makes it easier to
configure.



Adjustable Depths
24", 26.5", 29", 31.5", 34", 36"



OPEN FRAME FLOOR RACKS

2-POST
ALUMINUM & STEEL

SECTION
03



2PR 2-Post Open Frame Racks

| 2-POST ALUMINUM FRAME | 3FT. | 4FT. | 7FT. |
|--------------------------------------|-----------------|---|---|
| Item No. | FR1903-20-02 | FR1904-28-02 (Black) FR1904-28-03 (Silver) | FR1907-45-02 (Black) FR1907-45-03 (Silver) |
| Rack Size Height (Rack Units) | 40" (20U) | 54" (28U) | 84" (45U) |
| Rack Size Width | 21" | 21" | 21" |
| Rack Size Depth | Open | Open | Open |
| Mounting Format | 19" | 19" | 19" |
| Load Capacity | 400lbs | 500lbs | 1000lbs |
| Dual Mounting Rails | Tapped (#12-24) | Tapped (#12-24) | Tapped (#12-24) |
| Numbered RU positions | Yes | Yes | Yes |
| Electrostatic Powdercoat MicroFinish | Black | Black (-02 Only) | Black (-02 Only) |
| Screws & Washers | 12 each | 20 each | 40 each |
| Base Design | Floor Mount | Floor Mount | Floor Mount |
| Compliance | EIA-310D | EIA-310D | EIA-310D |
| Delivery Style | Knockdown | Knockdown | Knockdown |

| 2-POST STEEL FRAME | 7FT. | 7FT. |
|--------------------------------------|-------------------|-------------------|
| Item No. | FR1907-45-02SC | FR1907-45-02S |
| Rack Size Height (Rack Units) | 88" (45U) | 84" (45U) |
| Rack Size Width | 24" | 21" |
| Rack Size Depth | 24" | 22.5" |
| Mounting Format | 19" | 19" |
| Load Capacity | 1000lbs | 1000lbs |
| Dual Mounting Rails | Cage Nut (#12-24) | Cage Nut (#12-24) |
| Numbered RU positions | Yes | Yes |
| Electrostatic Powdercoat MicroFinish | Black | Black |
| Cage Nuts, Screws & Washers | 28 each | 28 each |
| Base Design | Casters | Floor Mount |
| Compliance | EIA-310D | EIA-310D |
| Delivery Style | Knockdown | Knockdown |

2PR Structure and Fabrication

| Item No. | Color | Rack Units (U) | Material | Posts | Side Rails (AWG) | Top Brackets (AWG) | Base (AWG) |
|------------------------------|--------|----------------|-------------------|-------|------------------|--------------------|------------|
| 2-POST ALUMINUM FRAME | | | | | | | |
| FR1903-20-02 | Black | 20U | 6063 T6 Aluminum | 2 | 5 | 5 | 2 |
| FR1904-28-02 | Black | 28U | 6063 T6 Aluminum | 2 | 5 | 5 | 2 |
| FR1904-28-03 | Silver | 28U | 6063 T6 Aluminum | 2 | 5 | 5 | 2 |
| FR1907-45-02 | Black | 45U | 6063 T6 Aluminum | 2 | 5 | 5 | 2 |
| FR1907-45-03 | Silver | 45U | 6063 T6 Aluminum | 2 | 5 | 5 | 2 |
| 2-POST STEEL FRAME | | | | | | | |
| FR1907-45-02S | Black | 45U | Cold Rolled Steel | 2 | 13 | 13 | 9 |
| FR1907-45-02SC | Black | 45U | Cold Rolled Steel | 2 | 13 | 13 | 13 |

OPEN FRAME FLOOR RACKS

2-POST

ALUMINUM & STEEL




2PR 2-Post Open Frame Racks

| Item No. | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Knockdown) |
|----------------|--|----------------------------------|-----|----|----------------------------------|-----|----|----------------------------|-----------------------------------|
| | | H | W | D | H | W | D | | |
| FR1903-20-02 | 20U | 40" | 21" | 3" | 35" | 19" | 3" | 400 | 18 |
| FR1904-28-02 | 28U | 54" | 21" | 3" | 49" | 19" | 3" | 500 | 21 |
| FR1904-28-03 | 28U | 54" | 21" | 3" | 49" | 19" | 3" | 500 | 21 |
| FR1907-45-02 | 45U | 84" | 21" | 3" | 79" | 19" | 3" | 1000 | 27 |
| FR1907-45-03 | 45U | 84" | 21" | 3" | 79" | 19" | 3" | 1000 | 27 |
| FR1907-45-02S | 45U | 84" | 21" | 3" | 79" | 19" | 3" | 1000 | 37 |
| FR1907-45-02SC | 45U | 88" | 24" | 3" | 79" | 19" | 3" | 1000 | 64 |

SECTION
03

2PR Floor Mount Holes



Standard racks are available with floor mount holes for mounting securely to floor.

2PR Locking Casters



Available in a caster version with locking casters for flexibility in relocation of the rack.

2PR Dual-Sided Rails



"U" shaped cage nut rail design to allow front and rear mounting of equipment.

2PR Reinforced Angled Top Braces



Reinforced angled top brace supports provide added load strength.

2PR Rack Unit Numbered Rails



Numbered rack units makes it easier to configure.





WALL MOUNT RACKS

2-POST

ADJUSTABLE, FIXED & SWING-OUT RACKS

SECTION

03



WMR Open Frame Wall Mount Racks

| | Fixed | Swing-Out | Adjustable |
|-------------------------------|-------------------------------------|------------------------|-------------------------------------|
| Rack Size Height (Rack Units) | 23" (13U) 28" (16U) 35" (20U) | 39" (20U) 48" (25U) | 20" (12U) 37" (18U) 49" (25U) |
| Post Rails | 2 | 2 | 2 |
| Rack Size Width | 21" | 21" | 21" |
| Rack Size Depth | 12" | 18" or 24" | 18" - 26" |
| Mounting Format | 19" | 19" | 19" |
| Dual Tapped Rails | Yes (#12-24) | Yes (#12-24) | Yes (#12-24) |
| Material | T6063 Aluminum | T6063 Aluminum | T6063 Aluminum |
| Base & Bracket (AWG) | 13 AWG | 13 AWG | 13 AWG |
| Side Rails (AWG) | 5 AWG | 13 AWG | 5 AWG |
| Powdercoat MicroFinish | Black | Black | Black |
| Screws & Washers (#12-24) | 16 each | 20 each | 16 each |
| Compliance | EIA-310D | EIA-310D | EIA-310D |
| Delivery Style | Knockdown | Knockdown | Knockdown |

WMR Open Frame Wall Mount Racks

| Item No. | Style | Rack Units (1U=1.75") | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Knockdown) |
|---------------|----------------------|-----------------------|----------------------------|-----|---------|----------------------------|-----|---------|----------------------|-----------------------------|
| | | | H | W | D | H | W | D | | |
| WR1922-13-02 | Fixed | 13U | 23" | 21" | 12" | 19.5" | 19" | 12" | 150 | 13 |
| WR1928-16-02 | Fixed | 16U | 28" | 21" | 12" | 24.5" | 19" | 12" | 165 | 15 |
| WR1928-20-02 | Fixed | 20U | 40" | 21" | 12" | 35" | 19" | 12" | 220 | 17 |
| SR1935-20-02 | Swing-Out | 20U | 40" | 21" | 18" | 35" | 19" | 18" | 80 | 46 |
| SR1935-20-02D | Swing-Out (Deep) | 20U | 40" | 21" | 24" | 35" | 19" | 24" | 80 | 46 |
| SR1943-25-02 | Swing-Out | 25U | 49" | 21" | 18" | 43.75" | 19" | 18" | 98 | 52 |
| SR1943-25-02D | Swing-Out (Deep) | 25U | 49" | 21" | 24" | 43.75" | 19" | 24" | 98 | 52 |
| SR1921-12-02 | Adjustable Swing-Out | 12U | 20" | 21" | 18"-26" | 15" | 19" | 18"-26" | 100 | 27 |
| SR1921-18-02 | Adjustable Swing-Out | 18U | 37" | 21" | 18"-26" | 32" | 19" | 18"-26" | 100 | 41 |
| SR1921-25-02 | Adjustable Swing-Out | 25U | 49" | 21" | 18"-26" | 43.75" | 19" | 18"-26" | 100 | 56 |

WMR Adjustable Depth Swing-Out Design



Available in Adjustable Depth version to accommodate deep mounted equipment. Swing-Out design for flexibility in accessing the back of the equipment.

WMR Swing-Out Design



Available in a Fixed or Swing-Out design for flexibility in accessing the back of the equipment.

WMR Dual-Sided Rails



"U" shaped 12-24 Tapped rail design to allow front and rear mounting of equipment.

WALL MOUNT BRACKETS



2-POST

HINGED & NON-HINGED

WMB Wall Mount Bracket Series

NEW BRACKET DESIGN

| | Non-Hinged | Hinged-Horizontal | Hinged-Vertical |
|--------------------------------------|---|--|--------------------------------------|
| Rack Size (Rack Units) | 3.5" (2U) 5.25" (3U) 7.0" (4U) 10.5" (6U) 12.25" (7U) | 1.75" (1U) 3.5" (2U) 5.25" (3U) 7.0" (4U) 10.5" (6U) | 3.5" (2U) 5.25" (3U) 7.0" (4U) |
| Rack Size Width | 20" | 20" | 19.5" |
| Rack Size Depth | 6" or 12" | 6" or 12" | 5"(2U), 7"(3U), 9"(4U) |
| Mounting Format | 19" | 19" | 19" |
| Hinged Swing Out Design | No | Yes | Yes |
| Dual Tapped Rails | Yes (#12-24) | Yes (#12-24) | Yes (#12-24) |
| Material | Cold Rolled Steel | Cold Rolled Steel | Cold Rolled Steel |
| AWG (Rails & Rear Plate) | 15 | 15 | 16 |
| Electrostatic Powdercoat MicroFinish | Black | Black | Black |
| Screws & Washers (#12-24) | 4 each | 4 each | 4 each |
| Compliance | EIA-310D | EIA-310D | EIA-310D |
| Delivery Style | Assembled | Assembled | Assembled |

SECTION
03



WMB Wall Mount Bracket Series

| Item No. | Rack Units (1U=1.75") 19" Format | External Dimensions (inch) | | | Internal Dimensions (inch) | | | Load Capacity (lbs.) | Shipping Weight (Assembled) | |
|------------|----------------------------------|----------------------------|----------|----------|----------------------------|----------|----------|----------------------|-----------------------------|------|
| | | H | W | D | H | W | D | | | |
| Non-Hinged | Hinged-Horizontal | | | | | | | | | |
| --- | WB19-0106H | 1U | 1.75" | 21" | 6" | 1.75" | 19" | 6" | 10 | 2 |
| WB19-0206N | WB19-0206H | 2U | 3.0" | 21" | 6" | 3.0" | 19" | 6" | 15 | 3 |
| WB19-0306N | WB19-0306H | 3U | 5.25" | 21" | 6" | 5.25" | 19" | 6" | 20 | 4 |
| WB19-0406N | WB19-0406H | 4U | 7.0" | 21" | 6" | 7.0" | 19" | 6" | 25 | 5 |
| WB19-0606N | WB19-0606H | 6U | 10.5" | 21" | 6" | 10.5" | 19" | 6" | 35 | 6 |
| WB19-0412N | WB19-0412H | 4U | 7.0" | 21" | 12" | 7.0" | 19" | 12" | 30 | 7 |
| WB19-0612N | WB19-0612H | 6U | 10.5" | 21" | 12" | 10.5" | 19" | 12" | 40 | 10 |
| WB19-0712N | --- | 7U | 12.25" | 21" | 12" | 12.25" | 19" | 12" | 45 | 11 |
| | Hinged-Vertical | | H | W | D | H | W | D | | |
| NEW | WV19-0205H | 2U | 6" | 19.5" | 5" | --- | 19" | --- | 35 | 4.4 |
| | WV19-0307H | 3U | 6" | 19.5" | 7" | --- | 19" | --- | 35 | 4.75 |
| | WV19-0409H | 4U | 6" | 19.5" | 9" | --- | 19" | --- | 35 | 5 |

WMB Hinged Design



Available in a Fixed or Swing-Out design for flexibility in accessing the back of the equipment. Hinged vertical brackets allow easy access to the back of the equipment.

WMB Extended Depth



"U" shaped #12-24 Tapped rail design to available in 6" or 12" depths for mounting deeper equipment.



EQUIPMENT SHELVING

SECTION

04

KEYBOARD SHELF
& Storage

ADJUSTABLE SHELF
Slide-Out & Adjustable

FIXED DUAL-SIDED SHELF
Vented & Solid

FIXED SINGLE-SIDED SHELF
Vented & Solid





EQUIPMENT SHELVING

KBS Keyboard Shelf Series

Page No.

KBS Series - Keyboard & Storage 45-46

SAS Adjustable Shelf Series

Page No.

SAS Series - Slide-Out & Adjustable 47-48

FDS Fixed Dual-Sided Shelf Series

Page No.

FDS Series - Vented & Solid

49

FSS Fixed Single-Sided Shelf Series

Page No.

FSS Series - Vented & Solid

50

SECTION

04



EQUIPMENT SHELVING

STORAGE SERIES

19" MOUNTING FORMAT

SECTION
04

KBS Storage Drawer with Key Lock

| | KBS SERIES | STANDARD DEPTH | EXTENDED DEPTH |
|--------------------------------------|------------|-----------------------------|-----------------------------|
| Item No. | | ES1319-0214 | ES1319-0414 |
| Unit Height (Rack Units) | | 3.5" (2U) | 7" (4U) |
| Rack Width | | 19" | 19" |
| Unit Depth | | 14" Closed 26.5" Open | 14" Closed 26.5" Open |
| Design Style | | Slide-Out | Slide-Out |
| Load Capacity | | 120 lbs. | 120 lbs. |
| Rack Attach Points | | 2 | 2 |
| Single Key Lock Set | | 2 keys per set | 2 keys per set |
| Material | | 18 AWG Cold Rolled Steel | 18 AWG Cold Rolled Steel |
| Electrostatic Powdercoat MicroFinish | | Black | Black |
| Screws & Washers (#12-24) | | 4 each | 4 each |
| Delivery Style | | No Assembly Required | No Assembly Required |



EQUIPMENT SHELVING

KEYBOARD SHELF SERIES

19" MOUNTING FORMAT



KBS Keyboard Shelf (with Reversible Mouse Tray)

KBS SERIES

| | |
|--------------------------------------|--|
| Item No. | ES1019-0108 |
| Unit Height (Rack Units) | 1.75" (1U) |
| Rack Width | 19" |
| Unit Depth | Keyboard: 8.25" Mouse: 6.75" |
| Design Style | Fixed Mount |
| Load Capacity | 12 lbs. |
| Rack Attach Points | 2 |
| Material | 18 AWG Cold Rolled Steel |
| Electrostatic Powdercoat MicroFinish | Black |
| Screws & Washers (#12-24) | 4 each |
| Delivery Style | Assembly Required *must attach Mouse Tray |

SECTION


04



KBS Hide-Away Monitor & Keyboard

KBS SERIES

| | |
|--------------------------------------|-----------------------------|
| Item No. | ES1119-0115 |
| Unit Height (Rack Units) | 3.5" (2U) |
| Rack Width | 19" |
| Unit Depth | 24" |
| Design Style | Slide-Out |
| Load Capacity | 65 lbs. |
| Rack Attach Points | 4 |
| Front Key Lock | No |
| Material | 16 AWG Cold Rolled Steel |
| Electrostatic Powdercoat MicroFinish | Black |
| Mounting Hardware | Included |
| Screws & Washers (#12-24) | 4 each |
| Delivery Style | No Assembly Required |





EQUIPMENT SHELVING

ADJUSTABLE SHELF SERIES

19" MOUNTING FORMAT

SECTION

04



SAS Extendable Shelf

SAS SERIES

| | |
|--------------------------------------|-------------------------------------|
| Item No. | ES1219-0218 |
| Unit Height (Rack Units) | 3.5" (2U) |
| Rack Width | 19" |
| Usable Shelf Depth (Adjustable) | 18" Collapsed 31" Extended (Max) |
| Design Style | Adjustable (Extendable) |
| Load Capacity | 120 lbs |
| Rack Attach Points | 4 |
| Material | 16 AWG Cold Rolled Steel |
| Electrostatic Powdercoat MicroFinish | Black |
| Screws & Washers (#12-24) | 8 each |
| Delivery Style | No Assembly Required |

SAS Adjustable Heavy Duty Shelf

COMPACT

STANDARD

| | | |
|--------------------------------------|-------------------------------|-------------------------------|
| Item No. | ES0519-0118 | ES0519-0126 |
| Unit Height (Rack Units) | 1.75" (1U) | 1.75" (1U) |
| Rack Width | 19" | 19" |
| Unit Depth | 18" Collapsed 26" Extended | 26" Collapsed 31" Extended |
| Usable Shelf Depth | 18" | 26" |
| Design Style | Slot Adjustable | Slot Adjustable |
| Load Capacity | 250 lbs | 250 lbs |
| Rack Attach Points | 4 | 4 |
| Material | 14 AWG Cold Rolled Steel | 14 AWG Cold Rolled Steel |
| Electrostatic Powdercoat MicroFinish | Black | Black |
| Screws & Washers (#12-24) | 8 each | 8 each |
| Delivery Style | No Assembly Required | No Assembly Required |



EQUIPMENT SHELVING

SLIDE-OUT SHELF SERIES

19" MOUNTING FORMAT



SAS Lightweight Slide-Out Shelf

SAS SERIES

| | |
|--------------------------------------|-------------------------------------|
| Item No. | ES0419-0114 |
| Unit Height (Rack Units) | 1.75" (1U) |
| Rack Width | 19" |
| Slide-Out Rail Depth | 14" Collapsed 28" Extended (Max) |
| Usable Shelf Depth | 14" |
| Design Style | Slide-Out |
| Load Capacity | 55 lbs |
| Rack Attach Points | 4 |
| Material | 16 AWG Cold Rolled Steel |
| Electrostatic Powdercoat MicroFinish | Black |
| Screws & Washers (#12-24) | 8 each |
| Delivery Style | No Assembly Required |

SECTION


04



SAS Heavy Duty Slide-Out Shelf

SAS SERIES

| | |
|--------------------------------------|-------------------------------|
| Item No. | ES0119-0123 |
| Unit Height (Rack Units) | 1.75" (1U) |
| Rack Width | 19" |
| Adjustable Rail Depth | 26" Collapsed 37" Extended |
| Usable Shelf Depth | 26" |
| Design Style | Adjustable & Slide-Out |
| Load Capacity | 150 lbs |
| Rack Attach Points | 4 |
| Material | 16 AWG Cold Rolled Steel |
| Electrostatic Powdercoat MicroFinish | Black |
| Screws & Washers (#12-24) | 8 each |
| Delivery Style | No Assembly Required |





EQUIPMENT SHELVING


FIXED DUAL-SIDED SHELF SERIES

19" MOUNTING FORMAT

SECTION 04


FDS 2-Piece Dual-Sided Shelf

| | VENTED | NON-VENTED |
|--------------------------------------|-----------------------------|-----------------------------|
| Item No. | ES0719-0225 | ES0919-0225 |
| Unit Height (Rack Units) | 3.5" (2U) | 3.5" (2U) |
| Rack Width | 19" | 19" |
| Unit Depth | 25" | 25" |
| Design Style | 2-Piece Fixed Mount | 2-Piece Fixed Mount |
| Rack Attach Points | 2 | 2 |
| Load Capacity | 120lbs | 130lbs |
| Material | Cold Rolled Steel 16 AWG | Cold Rolled Steel 16 AWG |
| Electrostatic Powdercoat MicroFinish | Black | Black |
| Screws & Washers (#12-24) | 8 each | 8 each |
| Delivery Style | No Assembly Required | No Assembly Required |



FDS 1-Piece Dual-Sided Shelf

| | VENTED | | NON-VENTED | |
|--------------------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| Item No. | ES0619-0218 | ES0619-0225 | ES0819-0218 | ES0819-0225 |
| Unit Height (Rack Units) | 3.5" (2U) | 3.5" (2U) | 3.5" (2U) | 3.5" (2U) |
| Rack Width | 19" | 19" | 19" | 19" |
| Unit Depth | 18" | 25" | 18" | 25" |
| Design Style | 1-Piece Fixed Mount | 1-Piece Fixed Mount | 1-Piece Fixed Mount | 1-Piece Fixed Mount |
| Rack Attach Points | 2 | 2 | 2 | 2 |
| Load Capacity | 90lbs | 120lbs | 100lbs | 130lbs |
| Material | Cold Rolled Steel 16 AWG | Cold Rolled Steel 16 AWG | Cold Rolled Steel 16 AWG | Cold Rolled Steel 16 AWG |
| Electrostatic Powdercoat MicroFinish | Black | Black | Black | Black |
| Screws & Washers (#12-24) | 8 each | 8 each | 8 each | 8 each |
| Delivery Style | No Assembly Required | No Assembly Required | No Assembly Required | No Assembly Required |



EQUIPMENT SHELVING

FIXED SINGLE-SIDED SHELF SERIES

19" MOUNTING FORMAT




FSS Fixed Single-Sided Shelf

| | VENTED | NON-VENTED | RACK SIZE HEIGHT (RACK UNITS) | RACK SIZE DEPTH | LOAD CAPACITY (LBS) |
|----------|-------------|-------------|----------------------------------|-----------------|------------------------|
| Item No. | ES0219-0107 | ES0319-0107 | 1.75" (1U) | 7" | 12 |
| | ES0219-0110 | ES0319-0110 | 1.75" (1U) | 10.5" | 15 |
| | ES0219-0210 | ES0319-0210 | 3.5" (2U) | 10.5" | 18 |
| | ES0219-0112 | ES0319-0112 | 1.75" (1U) | 12" | 20 |
| | ES0219-0212 | ES0319-0212 | 3.5" (2U) | 12" | 22 |
| | ES0219-0115 | ES0319-0115 | 1.75" (1U) | 15" | 35 |
| | ES0219-0215 | ES0319-0215 | 3.5" (2U) | 15" | 38 |
| | ES0219-0218 | - - - | 3.5" (2U) | 18" | 40 |
| | ES0219-0315 | ES0319-0315 | 5.25" (3U) | 15" | 41 |

SECTION
04

| | | |
|--------------------------------------|-------------------------|-------------------------|
| Rack Width | 19" | 19" |
| Design Style | Fixed Mount | Fixed Mount |
| Rack Attach Points | 2 | 2 |
| Material | Cold Rolled Steel 16AWG | Cold Rolled Steel 16AWG |
| Electrostatic Powdercoat MicroFinish | Black | Black |
| Screws & Washers (#12-24) | 4 each | 4 each |
| Delivery Style | No Assembly Required | No Assembly Required |





CABLE MANAGERS

FINGER DUCT STYLE CABLE MANAGERS

FOR FLOOR ENCLOSURES & OPEN FRAME RACKS



HCO Horizontal Finger Duct Cable Managers with Hinged Covers

| Item No. | HF19-01-40H | HF19-01-110DH | HF19-02-70H | HF19-02-190DH |
|--------------------------|---------------------------------------|--|---------------------------------------|--|
| Unit Height (Rack Units) | 1U (1.75") | 1U (1.75") | 2U (3.5") | 2U (3.5") |
| Mounting Format | 19" | 19" | 19" | 19" |
| Duct Size Depth | 3.38" | 6.75" | 3.38" | 6.75" |
| Finger Spacing | .625" | .625" | .625" | .625" |
| Design Style | Single Hinged Cover (Removable) | Dual-Sided Hinged Covers (Removable) | Single Hinged Cover (Removable) | Dual-Sided Hinged Covers (Removable) |
| Construction | Finger Duct | Dual Finger Duct | Finger Duct | Dual Finger Duct |
| Cable Capacity | 30 - 40 | 60 - 110 | 70 - 90 | 140 - 190 |
| Base Material | Cold Rolled Steel | Cold Rolled Steel | Cold Rolled Steel | Cold Rolled Steel |
| | 18AWG | 18AWG | 18AWG | 18AWG |
| Duct & Cover Material | ABS | ABS | ABS | ABS |
| Powdercoat MicroFinish | Black | Black | Black | Black |
| Pass Through Openings | 2 | 2 | 2 | 2 |
| Screws, Washers & Nuts | 4 each | 4 each | 4 each | 4 each |
| Delivery Style | No Assembly Required | No Assembly Required | No Assembly Required | No Assembly Required |

SECTION

05

LARGE OPENING FINGER DUCT



VCO Vertical Finger Duct Cable Managers with Hinged Covers

| Item No. | VF-04-200H | VF-04-240DH |
|--------------------------|---------------------------------------|--|
| Unit Height (Rack Units) | 22U (41") | 22U (41") |
| Mounting Format | Vertical | Vertical |
| Duct Size Depth | 6.5" | 11.9" |
| Finger Spacing | 1" | 1" |
| Design Style | Single Hinged Cover (Removable) | Dual-Sided Hinged Covers (Removable) |
| Construction | Finger Duct | Dual Finger Duct |
| Cable Capacity | 170 - 200 | 240 - 340 |
| Material | ABS | ABS |
| Powdercoat MicroFinish | Black | Black |
| Pass Through Openings | 4 | 4 |
| Mounting Brackets | 2 Included | 2 Included |
| Screws, Washers & Nuts | 4 each | 4 each |
| Delivery Style | No Assembly Required | No Assembly Required |



CABLE MANAGERS

FINGER DUCT STYLE CABLE MANAGERS

FOR FLOOR ENCLOSURES & OPEN FRAME RACKS



HCO Horizontal Finger Duct Style Cable Managers

| Item No. | SINGLE-SIDED FINGER DUCT | | | DUAL-SIDED FINGER DUCT |
|--------------------------------------|--------------------------|----------------------|----------------------|------------------------|
| | HF19-01-040 | HF19-01-050 | HF19-02-200 | HF19-02-200D |
| Unit Height (Rack Units) | 1.75" (1U) | 1.75" (1U) | 3.5" (2U) | 3.5" (2U) |
| Duct Size Height | 1.6" | 1.6" | 3.2" | 3.2" |
| Duct Size Depth | 2" | 2" | 3.2" | 6.4" |
| Mounting Format | 19" | 19" | 19" | 19" |
| Design Style | Single-Sided | Single-Sided | Single-Sided | Dual-Sided |
| Construction | Finger Duct | Finger Duct | Finger Duct | Finger Duct |
| Cable Capacity | 40 | 50 | 100 | 100 per side |
| Base Material | Cold Rolled Steel | Cold Rolled Steel | Cold Rolled Steel | Cold Rolled Steel |
| | 18AWG | 18AWG | 18AWG | 18AWG |
| Duct & Cover Material | PVC | PVC | PVC | PVC |
| Electrostatic Powdercoat MicroFinish | Black | Black | Black | Black |
| Screws & Washers (#12-24) | 4 each | 4 each | 4 each | 4 each |
| Delivery Style | No Assembly Required | No Assembly Required | No Assembly Required | No Assembly Required |

SECTION

05



VCO Vertical Finger Duct Style Cable Managers

| Item No. | FLOOR ENCLOSURES | | | OPEN FRAME FLOOR RACKS |
|--------------------------------------|----------------------|----------------------|----------------------|------------------------|
| | VF-04-100 | VF-07-100 | VF-07-140 | VR-07-140 |
| Unit Height | 48" | 72" | 72" | 72" |
| Duct Size Width | 1.6" | 1.6" | 2.2" | 2.2" |
| Duct Size Depth (Front/Back) | 4" | 4" | 6.4" | 6.4" |
| Mounting Format | Floor Enclosures | Floor Enclosures | Floor Enclosures | 2-Post Floor Racks |
| Design Style | Dual-Sided | Dual-Sided | Dual-Sided | Dual-Sided |
| Construction | Finger Duct | Finger Duct | Finger Duct | Finger Duct |
| Cable Capacity | 50 per side | 50 per side | 70 per side | 70 per side |
| Base Material | Cold Rolled Steel | Cold Rolled Steel | Cold Rolled Steel | Cold Rolled Steel |
| | 18AWG | 18AWG | 18AWG | 18AWG |
| Duct & Cover Material | PVC | PVC | PVC | PVC |
| Electrostatic Powdercoat MicroFinish | Black | Black | Black | Black |
| Screws, Washers & Nuts | 10 each | 10 each | 10 each | 10 each |
| Delivery Style | No Assembly Required | No Assembly Required | No Assembly Required | No Assembly Required |





CABLE MANAGERS

RING STYLE CABLE MANAGERS

FOR FLOOR ENCLOSURES & OPEN FRAME RACKS



HCO Horizontal Ring Cable Managers

NYLON RINGS

| Item # | HC19-01-050 | HC19-02-100 |
|--------------------------------------|-----------------------------|----------------------------|
| Unit Height (Rack Units) | 1.75" (1U) | 3.5" (2U) |
| Ring Size Height | 1.75" | 1.75" |
| Ring Size Depth (Front/Back) | 4" | 4" |
| Mounting Format | 19" | 19" |
| Design Style | Single-Sided Single Ring | Single-Sided Dual Ring |
| Cable Capacity | 50 | 100 |
| Base Material | Cold Rolled Steel 18AWG | Cold Rolled Steel 18AWG |
| Cable Rings | High Resistant Nylon | High Resistant Nylon |
| Electrostatic Powdercoat MicroFinish | Black | Black |
| Screws & Washers (#12-24) | 4 each | 4 each |
| Delivery Style | No Assembly Required | No Assembly Required |

SECTION

05



VCO Vertical D-Ring Cable Managers

VERTICAL D-RING

| Item No. | VD-00-034 | VD-00-070 |
|---------------------------|--|--|
| Unit Height (Rack Units) | 1.75" (1U) | 1.75" (1U) |
| Ring Size Width | 3.25" | 3.25" |
| Ring Size Depth | 3.25" | 5.7" |
| Mounting Format | Floor Enclosures & Open Frame Racks | Floor Enclosures & Open Frame Racks |
| Design Style | Single Rings | Single Rings |
| Cable Capacity | 34 | 70 |
| Cable Ring Material | High Resistant Nylon, Black | High Resistant Nylon, Black |
| Screws & Washers (#12-24) | 2 each | 2 each |
| Delivery Style | No Assembly Required | No Assembly Required |



VCO Vertical Ring Style Cable Managers

FLOOR ENCLOSURES ONLY

| Item No. | VC-06-050 |
|--------------------------------------|----------------------------|
| Unit Height | 72" |
| Ring Size Width | 1.75" |
| Ring Size Depth | 4" |
| Mounting Format | Floor Enclosures |
| Design Style | Dual-Sided Single Rings |
| Construction | Nylon Rings |
| Cable Capacity | 50 per side |
| Base Material | Cold Rolled Steel 18AWG |
| Cable Ring Material | High Resistant Nylon |
| Electrostatic Powdercoat MicroFinish | Black |
| Screws, Washers & Nuts | 10 each |
| Delivery Style | No Assembly Required |

ACCESSORIES

FILLER PANELS - 19" MOUNTING FORMAT
FOR FLOOR ENCLOSURES & OPEN FRAME RACKS



HFP Horizontal Brush Filler Panels

OPEN-BOTTOM BRUSH

| | |
|--------------------------------------|----------------------------|
| Item No. | HB19-01-025 |
| Unit Height (Rack Units) | 1.75" (1U) |
| Rack Size Width | 19" |
| Unit Depth | Flush |
| Design Style | Brush |
| Cable Capacity | 25 |
| Base Material | Cold Rolled Steel 18AWG |
| Cable Brushes | High Resistant Nylon |
| Electrostatic Powdercoat MicroFinish | Black |
| Screws & Washers (#12-24) | 4 each |
| Delivery Style | No Assembly Required |



SECTION

06

HFP Horizontal Solid Filler Panels

SOLID FILLER PANELS

| Item No. | BP19-01 | BP19-02 | BP19-03 |
|--------------------------------------|----------------------------|----------------------------|----------------------------|
| Unit Height (Rack Units) | 1.75" (1U) | 3.5" (2U) | 5.25" (3U) |
| Rack Size Width | 19" | 19" | 19" |
| Unit Depth | Flush | Flush | Flush |
| Design Style | Solid | Solid | Solid |
| Base Material | Cold Rolled Steel 18AWG | Cold Rolled Steel 18AWG | Cold Rolled Steel 18AWG |
| Electrostatic Powdercoat MicroFinish | Black | Black | Black |
| Screws & Washers (#12-24) | 4 each | 4 each | 4 each |
| Delivery Style | No Assembly Required | No Assembly Required | No Assembly Required |



HFP Horizontal Vented Filler Panels

VENTED FILLER PANELS

| Item No. | VP19-01 | VP19-02 | VP19-03 |
|--------------------------------------|----------------------------|----------------------------|----------------------------|
| Unit Height (Rack Units) | 1.75" (1U) | 3.5" (2U) | 5.25" (3U) |
| Rack Size Width | 19" | 19" | 19" |
| Unit Depth | Flush | Flush | Flush |
| Design Style | Vented | Vented | Vented |
| Base Material | Cold Rolled Steel 18AWG | Cold Rolled Steel 18AWG | Cold Rolled Steel 18AWG |
| Electrostatic Powdercoat MicroFinish | Black | Black | Black |
| Screws & Washers (#12-24) | 4 each | 4 each | 4 each |
| Delivery Style | No Assembly Required | No Assembly Required | No Assembly Required |





ACCESSORIES

VERTICAL AC POWER PDU'S

FOR FLOOR ENCLOSURES & OPEN FRAME RACKS

SECTION
06



VAC Vertical Rack Mounted Power Strips

| | 18 OUTLET | 30 OUTLET |
|---------------------------------|-------------------------|-------------------------|
| Item No. | VPS-1804 | VPS-3006 |
| Mounting Style | Vertical | Vertical |
| Height (Rack Units) | 48" (Adjustable Mounts) | 72" (Adjustable Mounts) |
| AC Rating | 125VAC / 15A | 125VAC / 20A |
| AC Wattage Rating | 1875W | 2000W |
| AC Frequency Rating | 60Hz | 60Hz |
| Built-In Amp Meter | No | Yes |
| Circuit Breaker Only | 15A | 20A |
| Max Output per Outlet | 12A | 16A |
| Power Cable Type | 15ft. 14/3C SJT | 15ft. 12/3C SJT |
| Surge Protection (EMI/RFI) | No | No |
| Surge Joule Rating | N/A | N/A |
| Power Indicator/Surge Indicator | Red LED | Red LED |
| Plug Type | NEMA 5-15P | NEMA 5-20P |
| Receptacle Type | NEMA 5-15R | NEMA 5-20R |
| AC Plug Location | 18 Front | 30 Front |
| Housing | Aluminum, Black | Aluminum, Black |
| RoHS Certified | Yes | Yes |
| UL Rating Certified | Yes (60950-1) | Yes (60950-1) |



VAC Vertical Mount Brackets



These adjustable vertical mount brackets mount onto the rack with one screw and the PDU easily snaps in place.

VAC 180° Swivel Power Cord



The 30 Outlet PDU is designed for heavier power loads to handle up to 25% more current than a standard AC outlet.

ACCESSORIES

HORIZONTAL AC SURGE PROTECTED PDU'S
FOR FLOOR ENCLOSURES & OPEN FRAME RACKS



HAC Horizontal Rack Mounted Surge Strips

20 AMP
14 OUTLET



| | 10 OUTLET | 12 OUTLET | 14 OUTLET |
|-----------------------------------|--------------------------|------------------------|--------------------------|
| Item No. | HPS-E10A | HPS-E12P | HPS-E14 |
| Mounting Style | Horizontal | Horizontal | Horizontal |
| Height (Rack Units) | 1.75" (1U) | 1.75" (1U) | 1.75" (1U) |
| AC Rating | 120VAC / 12A | 120VAC / 12A | 120VAC / 16A |
| AC Wattage Rating | 1440W | 1440W | 1920W |
| AC Frequency Rating | 60Hz | 60Hz | 60Hz |
| Outlet Placement | 2 Front / 8 Rear | 12 Front | 6 Front / 8 Rear |
| Switch w/Circuit Breaker | Yes | Yes | Yes |
| Circuit Breaker | 15A | 15A | 20A |
| Max Output per Outlet | 12A | 12A | 14A |
| Power Cable Type | 6ft. 14/3C SJT | 6ft. 14/3C SJT | 6ft. 14/3C SJT |
| Reversible 180 degree Swivel Cord | No | Yes | No |
| Surge Protection (EMI/RFI) | 3 Line (H-N, H-G, N-G) | 3 Line (H-N, H-G, N-G) | 3 Line (H-N, H-G, N-G) |
| Surge Joule Rating | 1050 joules | 1050 joules | 1050 joules |
| Power Indicator/Surge Indicator | Red LED/Green (Surge) | Red LED/Green (Surge) | Red LED/Green (Surge) |
| Plug Type | NEMA 5-15P | NEMA 5-15P | NEMA 5-20P |
| Receptacle Type | NEMA 5-15R | NEMA 5-15R | NEMA 5-20R |
| Safety Switch Guard | Yes | Yes | Yes |
| Housing | Cold Rolled Steel, Black | Plastic, Black | Cold Rolled Steel, Black |
| RoHS Certified | Yes | Yes | Yes |
| UL Rating Certified | Yes (60950-1) | Yes (60950-1) | Yes (60950-1) |

SECTION 06



HAC Vertical Mount Brackets



Both horizontal PDU's include vertical mount brackets which allow vertical mounting of these PDU's in a rack or enclosure.

HAC Safety Switch Guard



Designed into both horizontal PDU's, this safety switch guard protects against accidental tripping of the on-off switch.

HAC 180° Swivel Power Cord



Designed for tight spaces, the 12 outlet PDU has a built-in swivel power cord to allow mounting front or back of any 19" rack or enclosure.

10 OUTLET



12 OUTLET



14 OUTLET



20 AMP





ACCESSORIES

**VENTILATION DEVICES FOR ENCLOSURES
& GENERAL MOUNTING HARDWARE**

SECTION

06



FVU Floor Enclosure Ventilation Unit

4 FAN UNIT

| | |
|--------------------------|-----------------|
| Item No. | F19-6004 |
| Unit Height (Rack Units) | 1.75" (1U) |
| Rack Size Width | 19" |
| Unit Depth | 15.5" |
| AC Rating | 110VAC |
| AC Wattage Rating | 1440W |
| Power Cable Type | 6ft. 14/3C SJT |
| CFM Rating | 80 x 4 |



FVU 4" Boxer Fan

SINGLE FAN

| | |
|----------------|-----------------|
| Item No. | F04-6000 |
| Mounting Style | Screw Mount |
| Height | 4.7" |
| Length | 4.7" |
| Depth | 1.5" |
| AC Rating | 110VAC |
| CFM Rating | 60 |

HWA 12/24 Mounting Screws

MOUNTING SCREWS

| | |
|--------------------------------------|-----------------|
| Item No. | SCW-1224 |
| Screw Head Style | Phillips |
| Screw Size | #12-24 thread |
| Material | Steel |
| Electrostatic Powdercoat MicroFinish | Black |
| Package Quantity | 100 per bag |



HWA Cage Nut Rail Kits

CAGE NUT RAIL KITS

| | | |
|-----------------------------|-------------------|---------------|
| Item No. | RCN-42 | RCN-45 |
| Rack Unit Height | 73.5" (42U) | 79" (45U) |
| Numbered RU Positions | Yes | |
| Material | Zinc Plated Steel | |
| Screws, Nuts & Washers | 4 each | |
| Cage Nuts, Screws & Washers | 20 each | |
| Package Quantity | 1 pair | |



HWA Mounting Cage Nuts

MOUNTING CAGE NUTS

| | |
|------------------|-------------------------|
| Item No. | SCN-1224 |
| Material | Zinc Plated Steel |
| Size | 3/8" with #12-24 thread |
| Package Quantity | 50 per bag |



2PR 2-Post Rack Stabilizer Kit

2PR STABILIZER KIT

| | |
|--------------------------------------|-------------------|
| Item No. | RS-01-26 |
| Material | Cold Rolled Steel |
| | 14AWG |
| Screws, Nuts & Washers | 4 each |
| Electrostatic Powdercoat MicroFinish | Black |
| Package Quantity | 1 pair |



CABLE TRAY SYSTEM

WIRE MESH CABLE TRAYS
FOR CHANNELING FACILITY WIRING



CT Wire Mesh Cable Trays

| | |
|---------------------|------------------------------|
| Tray Length | 5ft 10ft |
| Material | Carbon Steel Q235 |
| Tray Wire Diameter | 0.18" (4.5 mm) |
| Finish / Coating | Electro Zinc Plating, Silver |
| Configurable | Yes (Cut-Bend-Clamp-Mount) |
| Application | Indoor |
| Accessories | Available Separately |
| UL Rating Certified | Yes |

AVAILABLE
5FT
LENGTHS



SECTION

07



CT Wire Mesh Cable Trays

| Item No. | Color | Length (ft) | Width (in) | Height (in) | Max Cable Load w/ Cat6 | Weight Capacity (lbs.) | Shipping Weight (lbs.) |
|-----------|--------|-------------|------------|-------------|------------------------|------------------------|------------------------|
| CT0504-03 | Silver | 5ft | 4" | 2" | 128 | 255 | 4.2 |
| CT1004-03 | Silver | 10.32ft | 4" | 2" | 128 | 510 | 8.4 |
| CT0506-03 | Silver | 5ft | 6" | 2" | 192 | 260 | 5.1 |
| CT1006-03 | Silver | 10.32ft | 6" | 2" | 192 | 520 | 10.1 |
| CT0508-03 | Silver | 5ft | 8" | 2" | 256 | 265 | 5.9 |
| CT1008-03 | Silver | 10.32ft | 8" | 2" | 256 | 530 | 11.9 |
| CT0512-03 | Silver | 5ft | 12" | 2" | 57 | 285 | 7.5 |
| CT1012-03 | Silver | 10.32ft | 12" | 2" | 57 | 570 | 15.0 |

HDC Heavy Duty Bolt Cutter

| | |
|--------------|---------------------------|
| ITEM NO. | CT0045 |
| Length | 18.5" |
| Material | Heavy Duty Steel |
| Function | Multi-Propose Bolt Cutter |
| Color | Red |
| Padded Grips | Black Rubber |





CABLE TRAY SYSTEM

CABLE TRAY ACCESSORIES & HARDWARE
FOR MOUNTING & CONFIGURING CABLE TRAYS

CT Cable Tray Couplers

SECTION


07



NUT & BOLT COUPLER

CT0001-03

(Hardware included)



BOLTLESS COUPLER

CT0009-03


(Hardware Not Required)



FAST LOCK COUPLER

CT0006-03

(Hardware Not Required)



STRENGTHENING BAR KIT

CT0002-03

(Hardware included)



FAST SPLICE BAR KIT

CT0007-03



FAST SPLICE HANDLE TOOL

CT0008-03



CORNER BAR COUPLER

CT0003-03

(Hardware included)



CURVED BAR COUPLER

CT0004-03

(Hardware included)



ADJUSTABLE COUPLER

CT0005-03

(Hardware included)



SPIDER COUPLER

CT0019-03



CENTRAL HOLD-DOWN

CT0031-03



M10 THREADED ROD COUPLER 1 1/2"

CT0051-1040-03




Requires Threaded 3ft Rod (CT0011-03)

CABLE TRAY SYSTEM

CABLE TRAY ACCESSORIES & HARDWARE
FOR MOUNTING & CONFIGURING CABLE TRAYS



CT Cable Tray Mounting Accessories

| | | |
|--|--|--|
|  <p>CEILING HANGING HOOKS CT0014-03 Requires Threaded 3ft Rod (CT0011-03)</p> |  <p>3/8" THREADED 3FT (1M) ROD CT0011-03 (Hardware Included)</p> |  <p>T CEILING HANGER CT0015-03 Requires Anchor Bolts (CT0046)</p> |
|  <p>I-BEAM MOUNTING CLAMP CT0016-03 Requires Threaded 3ft Rod (CT0011-03)</p> |  <p>CEILING HANGING BAR 4" CT0010-04-03 6" CT0010-06-03 8" CT0010-08-03 12" CT0010-12-03 Requires Threaded 3ft Rod (CT0011-03)</p> |  <p>CEILING HANGING BAR KIT 4" CT0013-04-03 6" CT0013-06-03 8" CT0013-08-03 12" CT0013-12-03 (ALL Hardware Included)</p> |
|  <p>FLAG CEILING BRACKET 4" CT0028-04-03 6" CT0028-06-03 8" CT0028-08-03 12" CT0028-12-03 Requires Anchor Bolts (CT0046)</p> |  <p>L WALL BRACKET 4" CT0025-04-03 6" CT0025-06-03 8" CT0025-08-03 12" CT0025-12-03 Requires Anchor Bolts (CT0046)</p> |  <p>T WALL BRACKET KIT 4" CT0022-04-02 6" CT0022-06-02 8" CT0022-08-02 12" CT0022-12-02 Requires Anchor Bolts (CT0046)</p> |
|  <p>V WALL BRACKET 4" CT0026-04-03 6" CT0026-06-03 8" CT0026-08-03 12" CT0026-12-03 Requires Anchor Bolts (CT0046)</p> |  <p>CABINET/FLOOR STAND 4" CT0017-04-03 6" CT0017-06-03 8" CT0017-08-03 12" CT0017-12-03 Requires Anchor Bolts (CT0046)</p> |  <p>FLAG FLOOR STAND 4" CT0029-04-03 6" CT0029-06-03 8" CT0029-08-03 12" CT0029-12-03 Requires Anchor Bolts (CT0046)</p> |

SECTION 07




CABLE TRAY SYSTEM

CABLE TRAY ACCESSORIES & HARDWARE
FOR MOUNTING & CONFIGURING CABLE TRAYS

CT Cable Tray Accessories & Hardware

SECTION

07




CABLE DROP GUIDE

CT0032-03



CABLE ROLLER GUIDE

CT0033-03



CABLE GUIDE TOP (STACKABLE)

CT0043

Requires Cable Guide Bottom (CT0044)




COPPER GROUNDING BOLT

CT0039



WHITE RUBBER END CAPS

CT0037-08



CABLE GUIDE BOTTOM

CT0044

Requires Cable Guide Top (CT0043)



ANCHOR BOLT 2-3/8"

CT0046



FLANGED HEX NUT

M8 CT0047-08-03

M10 CT0047-10-03



M10 HEX NUT

CT0048-10-03



M8 CARRIAGE BOLT 3/4"

CT0049-820-03



M10 FLANGED HEX BOLT

3/4" CT0050-1020-03

1 1/2" CT0050-1065-03



M10 THREADED ROD COUPLER 1 1/2"

CT0051-1040-03



Requires Threaded 3ft Rod (CT0011-03)

CABLE TRAY SYSTEM



CABLE TRAY CUTTING & BENDING GUIDES
CONFIGURING CABLE TRAYS FOR INSTALLATION





CROSS-JOINT:
SQUARE
CORNER




T CONNECTOR:
SQUARE
CORNER




T CONNECTOR:
ROUNDED





CROSS-JOINT:
ROUNDED
CORNER





ROUNDED
CORNER
4" - 100 mm
6" - 150 mm



ROUNDED
CORNER
8" - 200 mm



ROUNDED
CORNER
12" - 300 mm



SECTION
07



SAFETY PRECAUTION

Always use safety goggles and work gloves for your protection when installing cable tray!




CABLE TRAY SYSTEM



CABLE TRAY CUTTING & BENDING GUIDES
CONFIGURING CABLE TRAYS FOR INSTALLATION

SECTION
07


SQUARE CORNER



ANGLED CORNER



RADIAL CORNER




INTERNAL RISER





EXTERNAL RISER





ZIGZAG/SLOPE



ZIGZAG/SLOPE WITH BAR



REDUCER



SAFETY PRECAUTION

Always use safety goggles and work gloves for your protection when installing cable tray!

ITEM# INDEX

| Item No. | Page# | Item No. | Page# | Item No. | Page# | Item No. | Page# |
|--------------|-------|----------------|-------|----------------|-------|----------------|-------|
| BP19-01 | 54 | CT0048-10-03 | 61 | FE4219-42-02 | 7-8 | SR1943-25-02D | 41 |
| BP19-02 | 54 | CT0049-820-03 | 61 | FE4219-45-02 | 7-8 | VC-06-050 | 53 |
| BP19-03 | 54 | CT0050-1020-03 | 61 | FE4319-45-02 | 9-10 | VD-00-034 | 53 |
| CT0001-03 | 59 | CT0050-1065-03 | 61 | FE7019-34-02 | 11-12 | VD-00-070 | 53 |
| CT0002-03 | 59 | CT0051-1040-03 | 59,61 | FE7019-42-02 | 11-12 | VF-04-100 | 52 |
| CT0003-03 | 59 | CT0504-03 | 58 | FE7019-45-02 | 11-12 | VF-04-200H | 51 |
| CT0004-03 | 59 | CT0506-03 | 58 | FE7119-34-02 | 13-14 | VF-04-240DH | 51 |
| CT0005-03 | 59 | CT0508-03 | 58 | FE7119-42-02 | 13-14 | VF-07-100 | 52 |
| CT0006-03 | 59 | CT0512-03 | 58 | FE7119-45-02 | 13-14 | VF-07-140 | 52 |
| CT0007-03 | 59 | CT1004-03 | 58 | FE7219-42-02 | 15-16 | VP19-01 | 54 |
| CT0008-03 | 59 | CT1006-03 | 58 | FE7219-45-02 | 15-16 | VP19-02 | 54 |
| CT0009-03 | 59 | CT1008-03 | 58 | FE7319-42-02 | 17-18 | VP19-03 | 54 |
| CT0010-04-03 | 60 | CT1012-03 | 58 | FE7319-45-02 | 17-18 | VPS-1804 | 55 |
| CT0010-06-03 | 60 | ES0119-0123 | 48 | FE7419-28-02 | 19-20 | VPS-3006 | 55 |
| CT0010-08-03 | 60 | ES0219-0107 | 50 | FE7419-34-02 | 19-20 | VR-07-140 | 52 |
| CT0010-12-03 | 60 | ES0219-0110 | 50 | FE7419-42-02 | 19-20 | WB19-0106H | 42 |
| CT0011-03 | 59-61 | ES0219-0112 | 50 | FE7419-45-02 | 19-20 | WB19-0206H | 42 |
| CT0013-04-03 | 60 | ES0219-0115 | 50 | FR1903-20-02 | 39-40 | WB19-0206N | 42 |
| CT0013-06-03 | 60 | ES0219-0210 | 50 | FR1904-28-02 | 39-40 | WB19-0306H | 42 |
| CT0013-08-03 | 60 | ES0219-0212 | 50 | FR1904-28-03 | 39-40 | WB19-0306N | 42 |
| CT0013-12-03 | 60 | ES0219-0215 | 50 | FR1907-45-02 | 39-40 | WB19-0406H | 42 |
| CT0014-03 | 60 | ES0219-0218 | 50 | FR1907-45-02S | 39-40 | WB19-0406N | 42 |
| CT0015-03 | 60 | ES0219-0315 | 50 | FR1907-45-02SC | 39-40 | WB19-0412H | 42 |
| CT0016-03 | 60 | ES0319-0107 | 50 | FR1907-45-03 | 39-40 | WB19-0412N | 42 |
| CT0017-04-03 | 60 | ES0319-0110 | 50 | FR1924-28-02 | 37-38 | WB19-0606H | 42 |
| CT0017-06-03 | 60 | ES0319-0112 | 50 | FR1924-45-02 | 37-38 | WB19-0606N | 42 |
| CT0017-08-03 | 60 | ES0319-0115 | 50 | HB19-01-025 | 54 | WB19-0612H | 42 |
| CT0017-12-03 | 60 | ES0319-0210 | 50 | HC19-01-050 | 53 | WB19-0612N | 42 |
| CT0019-03 | 59 | ES0319-0212 | 50 | HC19-02-100 | 53 | WB19-0712N | 42 |
| CT0022-04-02 | 60 | ES0319-0215 | 50 | HF19-01-040 | 52 | WB-SE-02 | 34 |
| CT0022-06-02 | 60 | ES0319-0315 | 50 | HF19-01-050 | 52 | WM 3019-20-02D | 29-30 |
| CT0022-08-02 | 60 | ES0419-0114 | 48 | HF19-01-110DH | 51 | WM 3019-24-02D | 29-30 |
| CT0022-12-02 | 60 | ES0519-0118 | 47 | HF19-01-40H | 51 | WM 3019-28-02D | 29-30 |
| CT0025-04-03 | 60 | ES0519-0126 | 47 | HF19-02-190DH | 51 | WM2019-05-02 | 25-26 |
| CT0025-06-03 | 60 | ES0619-0218 | 49 | HF19-02-200 | 52 | WM2019-07-02 | 25-26 |
| CT0025-08-03 | 60 | ES0619-0225 | 49 | HF19-02-200D | 52 | WM2019-09-02 | 25-26 |
| CT0025-12-03 | 60 | ES0719-0225 | 49 | HF19-02-70H | 51 | WM2019-09-02D | 25-26 |
| CT0026-04-03 | 60 | ES0819-0218 | 49 | HPS-E10A | 56 | WM2019-11-02 | 25-26 |
| CT0026-06-03 | 60 | ES0819-0225 | 49 | HPS-E12P | 34,56 | WM2019-11-02D | 25-26 |
| CT0026-08-03 | 60 | ES0919-0225 | 49 | HPS-E14 | 56 | WM2019-14-02 | 25-26 |
| CT0026-12-03 | 60 | ES1019-0108 | 46 | HT6019-16-02 | 21-22 | WM2019-16-02 | 25-26 |
| CT0028-04-03 | 60 | ES1119-0115 | 46 | HT6019-30-02 | 21-22 | WM2019-20-02D | 25-26 |
| CT0028-06-03 | 60 | ES1219-0218 | 47 | JH-075-03 | 58 | WM2019-28-02D | 25-26 |
| CT0028-08-03 | 60 | ES1319-0214 | 45 | JH-13-03 | 58 | WM2119-07-02 | 27-28 |
| CT0028-12-03 | 60 | ES1319-0414 | 45 | JH-2-03 | 58 | WM2119-09-02 | 27-28 |
| CT0029-04-03 | 60 | EZ19-07-02 | 31-32 | JH-4-03 | 58 | WM2119-11-02 | 27-28 |
| CT0029-06-03 | 60 | EZ19-09-02 | 31-32 | RCN-42 | 57 | WM3019-07-02 | 29-30 |
| CT0029-08-03 | 60 | EZ19-11-02 | 31-32 | RCN-45 | 57 | WM3019-09-02 | 29-30 |
| CT0029-12-03 | 60 | F04-6000 | 57 | RS-01-26 | 57 | WM3019-09-02D | 29-30 |
| CT0031-03 | 59 | F19-6004 | 57 | SCN-1224 | 57 | WM3019-11-02 | 29-30 |
| CT0032-03 | 61 | FE4019-20-02 | 3-4 | SCW-1224 | 57 | WM3019-14-02 | 29-30 |
| CT0033-03 | 61 | FE4019-28-02 | 3-4 | SE0920-21-02 | 33-34 | WM3019-16-02 | 29-30 |
| CT0037-08 | 61 | FE4019-34-02 | 3-4 | SE0920-21-02A | 33-34 | WM3019-16-02D | 29-30 |
| CT0039 | 61 | FE4019-42-02 | 3-4 | SR1935-20-02 | 41 | WR1922-13-02 | 41 |
| CT0043 | 61 | FE4019-45-02 | 3-4 | SR1935-20-02 | 41 | WR1922-13-02 | 41 |
| CT0044 | 61 | FE4119-20-02 | 5-6 | SR1935-20-02D | 41 | WR1928-16-02 | 41 |
| CT0045 | 58 | FE4119-28-02 | 5-6 | SR1935-20-02D | 41 | WR1928-16-02 | 41 |
| CT0046 | 60,61 | FE4119-34-02 | 5-6 | SR1943-25-02 | 41 | WR1928-20-02 | 41 |
| CT0047-08-03 | 61 | FE4119-42-02 | 5-6 | SR1943-25-02 | 41 | WR1935-20-02 | 41 |
| CT0047-10-03 | 61 | FE4119-45-02 | 5-6 | SR1943-25-02D | 41 | | |



Distributed by:



www.QuestManufacturing.net

**LOAD UP USING
HIGH QUALITY!**



To View Our Full Line of Interconnect Products
Visit QuestTechnologyIntl.com